

**M.E. DEGREE EXAMINATIONS: JANUARY 2009**

First Semester

**COMMUNICATION SYSTEMS**

P07CM103 Optical Communication Networks

**Time: Three Hours****Maximum Marks : 100****Answer ALL Questions:-****PART A (20 x 1 = 20 Marks)**

1. An \_\_\_\_\_ network is typically a long haul network that interconnects cities or major traffic hubs.
 

A. Local-exchange network	B. Public network
C. Interexchange network	D. Private network
2. In fixed multiplexing, the bandwidth of all the virtual circuits on a link must \_\_\_\_\_ the link bandwidth.
 

A. less	B. equal	C. high	D. exceed
---------	----------	---------	-----------
3. The pumping process is more efficient, i.e, uses \_\_\_\_\_ pump power for a given gain, at \_\_\_\_\_ than these other wavelengths.
 

A. high, 1480nm	B. high, 980nm	C. less, 1480nm	D. less, 980nm
-----------------	----------------	-----------------	----------------
4. Example for reciprocal device
 

A. Isolators	B. Couplers	C. Circulators	D. Switches
--------------	-------------	----------------	-------------
5. \_\_\_\_\_ layer deals with the transport of the pathlayer payload and its overhead across the physical medium.
 

A. Path	B. Line	C. Section	D. Physical
---------	---------	------------	-------------
6. STS-1 SPE consists of \_\_\_\_\_ bytes.
 

A. 783	B. 873	C. 874	D. 784
--------	--------	--------	--------
7. ADM is a \_\_\_\_\_ that can multiplex or demultiplex various signals to or from an OC-N signal.
 

A. STE	B. LTE	C. PTE	D. MTE
--------	--------	--------	--------
8. SONET Frame has \_\_\_\_\_ rows and \_\_\_\_\_ columns of bytes with a total of \_\_\_\_\_ bytes.
 

A. 90, 9, 810	B. 90, 9, 8000	C. 9, 90, 8000	D. 9, 90, 810
---------------	----------------	----------------	---------------
9. Which one of the following is not a Broadcast and select network testbed?
 

A. NTT	B. Lambdanet	C. Rainbow	D. AfricaONE
--------	--------------	------------	--------------

10. Maximum propagation delay from any node to star in MAC protocol is \_\_\_\_\_.
- A.  $d_{prop} * 2$                       B.  $d_{prop}$                       C.  $d_{prop}/2$                       D.  $d_{prop}/4$
11. Two most popular topologies for broadcast and select networks are
- A. Ring & mesh                      B. Star & Bus                      C. Ring & bus                      D. Ring & star
12. The \_\_\_\_\_ is defined as the delay between the time at which a packet is available for transmission at a node and the time at which it is first transmitted.
- A. Propagation delay                      B. Access delay  
C. Queuing delay                      D. Transmission delay
13. Key element in the wavelength routing network is \_\_\_\_\_.
- A. WXC                      B. Optical ADM                      C. ADM                      D. Regenerator
14. Topology of a wavelength routing network is \_\_\_\_\_.
- A. Ring                      B. Bus                      C. Star                      D. Arbitrary mesh
15. Which one of the regeneration technique essentially produces a fresh copy of the signal at each regeneration step?
- A. 1R                      B. 4R                      C. 2R                      D. 3R
16. \_\_\_\_\_ is the process aligning two pulse streams in time.
- A. Synchronization                      B. Delay                      C. Tunable delay                      D. Fixed delay
17. In Routing and wavelength assignment, an undirected edge can represent a \_\_\_\_\_ fiber link with transmission in \_\_\_\_\_ directions over a single fiber.
- A. Bidirectional, both                      B. Bidirectional, only one  
C. Unidirectional, both                      D. Unidirectional, only one
18. BT lab testbeds using \_\_\_\_\_ multiplexing.
- A. byte interleaved                      B. bit interleaved  
C. packet interleaved                      D. string interleaved
19. TBONE testbed using \_\_\_\_\_ topology
- A. Star                      B. Bus                      C. Crossbar                      D. Mesh
20. \_\_\_\_\_ achieved by using a fiber of the appropriate length.
- A. Throughput                      B. Synchronization                      C. Delay                      D. No. of Hops

**PART B (5 x 16 = 80 Marks)**

21. (a) (i) Compare Regenerators and Amplifiers. (8)

(ii) Discuss about construction, principle of operation and pumping Details of EDFA. (8)

**(OR)**

21. (b) (i) List out the Optical fiber components. Explain the principle of operation of Isolators. (10)

(ii) List out the important parameters that are used to characterize the suitability of a switch for optical networking applications. (6)

22. (a) (i) Draw the neat sketch of SONET frame structure. (8)

(ii) Explain about SONET STS-1 SPE. (8)

**(OR)**

22. (b) (i) Define SONET Network elements. Explain about any two of SONET network elements (12)

(iii) Compare UPSR and two fiber BLSR. (4)

23. (a) Explain about MAC protocol and its synchronization details.

**(OR)**

23. (b) (i) Compare Slotted Aloha/Slotted Aloha Protocol over DT-WDMA. (6)

(ii) Explain any 2 of the broadcast and select network testbeds. (10)

24. (a) Discuss in detail about wavelength routing network node designs.

**(OR)**

24. (b) (i) Write short notes about the optical layer features. Compare Optical and electronic WXC. (8)

(ii) Write short notes about Routing and wavelength assignment problem. (8)

25. (a) Write short notes about (1) Buffering (2) Deflection routings of switch based networks.

**(OR)**

25. (b) (i) Discuss about OTDM synchronization. (8)

(ii) Compare SDM/TDM over WDM approach. (8)

\*\*\*\*\*