

Reg. No. :

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

R 3338

B.E./B.Tech. DEGREE EXAMINATION, NOVEMBER/DECEMBER 2007.

Fourth Semester

Mechatronics Engineering

EE 1264 — CONTROL SYSTEMS

(Regulation 2004)

Polar, Semilog graph sheets are to be provided.

Time : Three hours

Maximum : 100 marks

Answer ALL questions.

PART A — (10 × 2 = 20 marks)

1. What are basic elements of translational and rotational mechanical system?
2. State Mason's gain formula.
3. Mention any four time-domain specifications.
4. What is meant by steady-state error?
5. Define : Phase margin.
6. What is meant by all pass system?
7. How is stability related to location of roots in s-domain?
8. How is Nyquist stability criterion used to determine closed loop stability of systems?
9. What is meant by compensation?
10. How is time-domain specifications converted into a pair of dominant root locations?

PART B — (5 × 16 = 80 marks)

11. (a) Obtain the transfer function of the following mechanical system (figure 1).




Figure 1 Qn. 11 (a)

Or

- (b) For the system represented by the following equations, find the transfer function $X(s)/U(s)$ by signal flow graph technique.

$$\begin{aligned}x &= x_1 + \beta_3 u \\ \dot{x}_1 &= -a_1 x_1 + x_2 + \beta_2 u \\ \dot{x}_2 &= -a_2 x_2 + \beta_1 u\end{aligned}$$

12. (a) Figure 2 shows a system employing proportional plus error-rate control. Determine the value of the error-rate factor K_e so that the damping ratio is 0.5. Determine the values of settling time, maximum overshoot and steady-state error (for unit ramp input) with and without error-rate control. Comment upon the effect of error-rate control on system dynamics.




Figure 2 Qn. 12 (a)

Or

- (b) A unity feedback system is characterized by the open-loop transfer function $G(S) = \frac{10}{S(0.1S+1)}$. Determine the steady state errors for unit-step, unit-ramp, and unit-acceleration input. Also evaluate the dynamic error of the system when subjected to an input given by the polynomial $r(t) = a_0 + a_1 t + \frac{a_2}{2} t^2$.

13. (a) Sketch the Bode plot for the following transfer function and determine gain margin & phase margin $G(S) = \frac{10}{S(1+0.5S)(1+0.1S)}$.

Or

- (b) Consider the feedback system shown in figure 3.




Figure 3 Qn. 13 (b)

- (i) Find the value of 'K' and 'a' to satisfy the following frequency domain specifications $M_r = 1.04$ and $\omega_r = 11.55$ rad/sec
- (ii) For the values of 'K,' and 'a' determined in part (i), calculate the settling time and bandwidth of the system.

14. (a) A unity feedback control system is characterized by the open-loop transfer function $G(S) = \frac{K(S+13)}{S(S+3)(S+3)}$

- (i) Using the Routh criterion, calculate the range of values of K for the system to be stable.
- (ii) Check if for $K = 1$, all the roots of the characteristic equation of the above system have damping factor greater than 1.

Or

- (b) Draw the root-locus plot for the following open-loop transfer function

$$G(S) = \frac{K}{S(S+4)(S^2+4S+20)}$$

15. (a) Write the steps involved in lead compensator design using frequency domain approach

Or

- (b) Write the steps involved in lag compensator design using time domain approach