

B.E./B.Tech. DEGREE EXAMINATION, MAY/JUNE 2006.

Sixth Semester

Civil Engineering

CE 336 --- STRUCTURAL ANALYSIS --- II

Time : Three hours

Maximum : 100 marks

Answer ALL questions.

PART A --- (10 × 2 = 20 marks)

1. Draw the influence line diagram for the reactions of a simply supported beam 8 m span.
2. Draw the influence line for bending moment at a section 4 m from the fixed end of a cantilever beam of span 10 m.
3. Draw qualitative influence line diagrams for the reactions in a fixed beam of span 6 m.
4. Find the bending moment at a section 4 m from the left end of a three hinged parabolic arch due to UDL of 10 kN/m over entire span 30 m.
5. Derive the expression for horizontal thrust in a three hinged parabolic arch carrying UDL over entire span.
6. What is shape factor?
7. What is plastic hinge?
8. A uniformly distributed load of 10 kN/m, 5m length crosses a simply supported beam having a span of 4 m. Find the maximum bending moment at mid-span.
9. Find the maximum bending moment at a section 30 m from the left end of the three hinged stiffening girder of span 100 m when a UDL of 10 kN/m, 5 m length crosses the girder.
10. Define tension coefficient.

PART B (5 × 16 = 80 marks)

11. (i) Draw the influence line for reaction at B of the continuous beam ABC simply supported at A and C using Muller Breslau's principle. AB = 3 m, BC = 4 m. EI is constant.
- (ii) Draw the influence line for reaction at A of the beam described above.
12. (a) Analyse the space truss shown in Fig. Q. 12 (a) using tension coefficient method. The coordinates of joints are A (0, 0, 0), B (6, 0, 0), C (6, 3, 0), D (0, 3, 0), E (2, 1.5, 4) and F (4, 1.5, 4). Determine the forces in the members of the truss.




Fig. Q. 12 (a)

Or

- (b) Analyse the curved beam in plan shown in Fig. 12 (b) and draw the SFD and BMD. (Note : P is vertical load).




Fig. 12 (b)

13. (a) Derive the expression for horizontal thrust in a two hinged parabolic arch carrying a point load P at distance one fourth span from left support. Assume $l = l_0 \sec \theta$.

Or

- (b) A three hinged parabolic arch having span 20 m, Rise 4 m carries a UDL of 30 kN/m over the left half of the span. Draw the BMD. Also find the normal thrust and radial shear at a section 4 m from the left support.

14. (a) A suspension cable with 70 m span and 7 m dip is stiffened by a three hinged girder. The dead load is 15 kN/m. Find shear force and bending moment to the girder at a section 10 m from the left hand hinge when a point load of 100 kN is placed at 3 m from the left end using influence line diagrams.

Or

- (b) Determine the forces in the members of the space frame plan view is shown in Fig. Q. 14 (b) by tension coefficient method. The coordinates are A (0, 0, 0), B (0, 6, 0), C (9, 3, 0), D (6, 3, 5). A, B, C are hinged supports at same level. A vertical load of 100 kN is applied at D.




Fig. Q. 14 (b)

15. (a) Derive the shape factor for the triangular cross section.

Or

- (b) Determine the plastic moment capacity required for the frame shown in Fig. Q. 15 (b).




Fig. Q. 15 (b)