

# AMBIENT INTELLIGENCE WITHIN AN ENVIRONMENT

PROJECT REPORT

MARCH-2003

P-883

SUBMITTED IN PARTIAL FULFILLMENT OF THE  
REQUIREMENTS FOR THE AWARD OF THE DEGREE OF  
**BACHELOR OF ENGINEERING**

*Submitted by*


Bhargavy Gananathan

Nithya.V

Palliyil Veena Ravindranath

*Under the guidance of*

Mr.K.R.Baskaran, B.E.,M.S.



DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

*KUMARAGURU COLLEGE OF TECHNOLOGY*

COIMBATORE-641006

KUMARAGURU COLLEGE OF TECHNOLOGY

Coimbatore-641006

**CERTIFICATE**

This is to certify that project report entitled  
'AMBIENT INTELLIGENCE WITHIN AN ENVIRONMENT'  
is a bonafide record of work done by:


Bhargavy Gananathan - 9927S0048

Nithya.V - 9927S0062

Palliyil Veena Ravindranath - 9927S0063

in partial fulfillment of the requirements for the award of  
Bachelor of Engineering.

  
Head of the Department

  
Staff in charge

Submitted for the University Examination held on 20-3-2023

Internal Examiner

External Examiner

PLACE: COIMBATORE

DATE: 20-3-2023

## ACKNOWLEDGEMENT

The success accomplished in this project would have not been possible without the timely help and guidance rendered by many people to whom we feel obliged and grateful. We wish to express our sincere and heartfelt gratitude to these personalities.

Dr. K.K. Padmanabhan B.Sc., (Engg) M.Tech., Ph.D., Principal, Kumaraguru College of Technology, Coimbatore for permitting us to undertake the project.

We also thank Dr. S.Thangasamy, Ph.D., Head of Department of computer Science and Engineering, Kumaraguru College of Technology and Mrs. S.Devaki, M.S., Assistant Professor for providing us guidance and making this project a successful one.

We wish to express our sincere gratitude to our project guide Mr.K.R.Baskaran,B.E.,M.S., for the interest and the support he gave us towards the completion of this project successfully.

Our deepest gratitude goes to Mrs.N.Chitra Devi M.E., Lecturer and all other staff of our department for their unrestrained attention at all stages to make this project a successful one. The motivation provided by all the staff remained a milestone for the completion of this project.

We express our sincere gratitude to Mr.Jaykumar, Mr.Balaji and other members of Cyber Soft India, Coimbatore, for their valuable support and guidance throughout the course of this project.

Our parents and all our friends deserve particular thanks for helping us out in various ways. Without their valuable assistance, this project would have fallen short of schedule and requirements.

There are so many people, so many minds all of whom have extended their hands to us in some way or the other. Neither words can express nor pages can fill our sincere gratitude.

## CONTENTS

1. INTRODUCTION.....	1
❖ Current status of the problem taken up	
❖ Relevance and Importance	
2. LITERATURE SURVEY.....	4
3. SOFTWARE REQUIREMENTS.....	5
4. PROPOSED APPROACH TO THE PRODUCT.....	10
5. DETAILS OF THE DESIGN.....	11
6. IMPLEMENTATION DETAILS.....	13
❖ Remote Desktop Capturing	
❖ Device Control and Programming	
❖ Interaction over the Internet	
7. TESTING.....	20
❖ Unit testing	
❖ Integration testing	
❖ User Acceptance testing	
8. CONCLUSION.....	23
9. FUTURE OUTLOOK.....	24
10. APPENDIX.....	25
❖ Block Diagram	
❖ Circuit Diagram	
❖ Sample Forms	
❖ Sample Coding	
❖ Glossary of terms	
11. REFERENCES	

# 1. INTRODUCTION

## **Current status of the problem taken up**

Today's system is one in which man must adapt to the appliances. Hence, work becomes tedious, time consuming and of course, less interactive.

Tomorrow's system, that is, the system that we have developed is one, which adapts to man's needs.

In the existing system, remote controls, smart cards etc are used. The 'Blue tooth' technology has been adapted. But, all these features have their own disadvantages. Taking the case of remote controls, it can be operated at a limited distance only. But, we have aimed at enabling the possibility of controlling the appliances from anywhere in this world. If we consider, the smart cards, the cost factor is a major drawback. Moreover, it has to be treasured safely.

Coming to the device controller, the present systems use the X-10 signal receptor which pose a major set back in the economy factor for most of our people. We have designed a circuit, which can be used as an alternative with a nominal rate.

Our system serves as a platform for remote control of various appliances by connecting arbitrary appliances through various arbitrary connections. Hope! It would act as a user- friendly system.

## **Relevance and importance**

After getting the results of initial study, the investigation is expanded to more detailed feasibility study. The objectives at this stage are to provide solutions to the stated problems usually in the form of specifications to meet the user requirements and make recommendations for a new computer based system.

The system has been evaluated from a technical point of view first and if technically feasible, the system is tested for social and economic compatibility.

### ***Technical Feasibility***

The system is developed using Visual Basic 6.0, Web tools: HTML and ASP

### ***Social Feasibility***

The assessment of social feasibility is done along technical feasibility. Our project is developed in such a way that a user can use it very flexibly.

### ***Economic Feasibility***

Our system is justified by cost and benefit criteria to ensure that efforts is concentrated on projects, which will give test return at the earliest opportunity.

### ***Interactive System***

Perfect analysis is made by finding out what happens in the existing system, deciding what changes and new features are to be added and then defining exactly what the new system must do. The system analysis is largely concerned with determining, developing and agreeing to user's requirements and selecting those to be satisfied by an interactive solution. Prime opportunity to communicate with the users and conceive a join understanding of what the system should be doing, together with a view of the relative importance of the system features has been provided.

### *Advantages*

The system is user friendly with improved efficiency. The advantages are listed below:

- ❖ *Adaptability*

The system adapts to the user requirements.

- ❖ *Mobility*

The system can be used in any environment.

- ❖ *Modularity*

Our system is developed using a hierarchical approach by dividing into smaller modules.

## 2. LITERATURE SURVEY

A similar project was carried out using Perl and CGI programming. Though, it had its own advantages, there are so many nifty shortcuts built into the Perl that we generally can accomplish a lot more in a lot less code in Visual Basic.

Perl's string-manipulation functions are complex that it's almost ridiculous to try. It is not an exaggeration to say that 90% of CGI programs involve heavy string manipulation.

On the contrary Visual Basic which is familiar to just about anyone who has ever done programming. It is easy to learn easy to use, it is fast and is popular. Above all, in a totally Microsoft environment, it can work quickly and efficiently.

Setting aside the software part, if we look into the hardware. I.e., the device controller, it was developed using x-10 signal receptor. This is costly equipment. Now, we have devised this controller keeping the cost factor in mind.

We obtained a good experience during the course of the project. It has strengthened our team spirit and has provided us with practical knowledge of how a hardware system is designed. In short it was a novel experience for us all.

### **3. SOFTWARE REQUIREMENTS**

We have mainly used Visual Basic language in the Windows 98 operating system. The web tools used are HTML and ASP.

#### **Introduction to Visual Basic**

Visual Basic (6.0) is the newest addition to the family of Visual Basic products. Microsoft Visual Basic is the quickest and easiest way to create powerful application for Microsoft windows operating system. The VB programming system allows creating robust and useful applications that fully make use of the graphical User Interface (GUI). VB provides graphical environment in which we can visually design the forms and controls that become the buildings block of the application. VB supports many useful tools that will help us to be more productive.

Version 6.0 of VB is specifically designed to utilize the Internet. It comes with several controls and allows creating web-based applications called Active X executables.

New to VB 6.0 are the ISAPI application and dynamic HTML project templates. These templates provide a framework to develop server-side components as well as “smart web pages and applications”.

Visual Basic continues to support the explorer style development environment modeled after windows explorer. This makes it easy for a computer user to jump right into creating applications with VB. Using VB powerful full-featured applications can be created.

Data access features allows to create database and front end applications for most popular database formats.

## **Windows 98**

Windows 98 offers many new and exciting features in addition to any features from earlier versions of windows. Most important feature is it's flat 32 bit addressing. Windows 98 is a pre-emptive, multitasking to perform several actions at the same time. The advantages are powerful, mobile computing features using the Microsoft Network, a recycle bin for storing deleted files, and the inbox, which can be used for communication like fax, e-mail.

The other features are:

### ***New improved interface***

Windows 98 features the task button and task bar. Start button can be used to quickly open programs, find documents and use system tools. Task bar is used to switch between programs.

### ***Windows Explorer***

Windows explorer is a powerful way to browse through and manage our files, drives, and windows explorer is a powerful through and manage our files, drives and networks.

### ***Improved multimedia support***

We can enjoy the faster void capability for games, enhanced support for MS-DOS based games and improved performance for playing video based sound files.

### ***Microsoft Exchange***

We can use Microsoft exchange to view and work with all types of electronic communication including e-mail and faxes.

### ***Microsoft Network***

We can use this new, affordable, and easy to use online service to communicate with the people worldwide, using e-mail, bulletin boards, and the Internet.

### ***Scan disk***

The scan disk is used to check the hard disk for errors and fix the problems that are around.

### ***Drive space***

This is to compress the disk.

### **ASP**

Active Server Pages (ASP) technology is actually a very simple idea. ASP let us to use the power of a web server to process user requests and provide dynamic, individualized content based on logic, file and database data, and also process the users individualized data. In other words, ASP lets multiple users simultaneously run a program on your web server.

ASP treats users as unique entities, even though all of them are running the same program on the same machine – our web server. Obviously, running a complex program for multiple users on one computer takes a lot of resources. Fortunately, Microsoft makes sure those resources are at our disposal. ASP provides:

- ❖ A way to save individualized data for each user
- ❖ Access to the file system
- ❖ Access to databases
- ❖ A means to launch and control any component object model (COM) component.

In short, ASP allows you to build multi user applications, which means we can leverage ASP to provide application scalability. If we plan our ASP applications carefully, they can scale from a single-server application that can handle 30-100 simultaneous users and a few thousand hits per day to multi-server (web farm) applications handling thousands of simultaneous users and millions of requests per day.

ASP isn't a single technology. Using ASP effectively requires that we learn a collection of tools, languages, techniques, and technologies.

### *Benefits of ASP*

- ASP is language independent.
- ASP is for non-programmers.
- ASP code resides in text files.
- ASP code times out.
- ASP code is server-safe.
- ASP code doesn't require registration.
- ASP applications are usually small.
- We can upgrade ASP applications without stopping IIS.

### **HTML**

In keeping with the original and ongoing theme of the Internet -- openness and portability; HTML was developed. We can create, edit, or view the HTML code for a web page in any text-editor on any computer platform, such as windows notepad.

Although creating simple web pages in a text editor is easy, it can quickly turn into a grueling and mind-numbing task. That's why there are web-authoring tools such as Microsoft Front Page express and Macromedia Dream weaver, to create web pages in the same way as we create documents in word processor.

When we open a web page in our browser, we don't see the HTML code, instead, the browser interprets the HTML code and displays the page appropriately on the screen. If we are creating a web page in a text editor and want to view the file, then we have to save it and open in our browser. Then, we can continue to edit, save ones work, and view the results, switching back and forth between the text editor and the browser to see the effects.

The original intent of the HTML specification was to allow web authors to describe the structure of a page without spending too much time worrying about the look of the page-that part of the job was left to the browsers. Traditionally, each browser had it's own way of interpreting the look of the page, and web authors had to live with the fact that pages they created might appears somewhat differently in different browsers.

#### 4. PROPOSED APPROACH TO THE PRODUCT

##### Software Configuration

LANGUAGE	:	VISUAL BASIC 6.0
OPERATING SYSTEM	:	WINDOWS 98
WEB TOOLS	:	HTML, ASP

##### Hardware Configuration (server)

- RD DISK: CPU:PIII 500 MHZ
- HA41 GB SCSI
- MAIN MEMORY : 256 MB
- DISPLAY : 15"
- KEYBOARD : 104 KEYS
- MOUSE : PS/2 SCROLL MOUSE
- DISKDRIVE: 1.44 MB
- CD DRIVE: 1.44 MB
- CD DRIVE : 52X
- MODEM : ISDN
- PRINTER



##### Hardware Configuration (client)

- CPU: PIII 500 MHZ
- HARD DISK : 41 GB SCSI
- MAIN MEMORY 256 MB
- DISPLAY : 15"
- KEY BOARD : 104 KEYS
- MOUSE : PS/2 SCROLL MOUSE
- DISKDRIVE: 1.44 MB
- CD DRIVE:52 X
- MODEM: ISDN

## 5. DETAILS OF THE DESIGN

The whole project is basically divided into three modules and finally integrated to bring about a full-fledged interactive system. The three modules are

- ❖ Remote Desktop Capturing
- ❖ Device Control and Programming
- ❖ Interaction over the internet

### **Remote Desktop Capturing**

This is done within a LAN environment while one system acts as a client and the other acts as a server.

#### *Client Side*

A socket is first created and bound to the server port. After a smooth connection, user name and password is sent as data to the remote server. After successful login, sending a request data captures the remote desktop. The request is got after which the mouse ports and keyboard is connected. Then synchronization operations are done properly.

#### *Server Side*

A socket is created for any port and is made to listen during program initialization. The ports are watched continuously for any incoming data. The username and password are verified and an acknowledgement is sent, otherwise it is rejected. Then the result is got, processed and the results are returned. New ports are opened for the keyboard and mouse. Lastly, the win32 API functions are called to perform the operations.

## **Device control and Programming**

A simple hardware interface circuit and its driver software is developed to control the appliance with the help of relays. For checking the current status interactively, a software stimulator of the device controller is produced.

The hardware consists of ten easily available discrete ICs wired up for operating up to seven electrical devices. The software comprises mainly the graphics portion for a GUI (Graphics User Interface) based system. Control software has been written for one device only at present and can be expanded for control of more devices in the like manner. The circuit uses printer port 378 (hex) as output and 379h as input port. Thus, the device control and programming is done.

## **Interaction over the Internet**

This module deals with how a user can get access to the server through the Internet and thus control the appliances connected to the device controller.

For this, an interactive web page is designed for the user, which is accessed by him after proper validity tests are performed.

Thus the user can view the status of each device as well as change the status depending on the requirements.

*IMPLEMENTATION*

*DETAILS*

## 6. IMPLEMENTATION DETAILS

### Remote Desktop Capturing

This module deals with accessing the device controller within a LAN Network.

LAN Network is where all the computers located at a particular distance from one another communicates with each other. The idea proposed here is Remote Desktop Capture where by we capture the current desktop of the system to which the device controller is connected.

For the remote desktop capture two software namely the client side program & the server side program are written. The server program must always be in the running mode at the server. Any client on the network can access this server by means of obtaining the IP address of the server. Once the IP address of the server is known, we then connect to the remote server by means of a password and username. The password and username at the client side must be same as the one used by the user to login at the server.

All the ports at the server side are in the 'listen' mode. Once authentication is verified, then we can enter the remote server through these ports that are listening. The client program will then establish a connection with the server through these ports and hence transmission and reception of data begins.

We have implemented this module using the front-end tool Visual Basic 6.0. However, we have used a number of VC++ functions by importing the libraries to Visual Basic. The system libraries of VC++ make the Remote Desktop Capturing less complex.

Once the connection between the client & the server has been established, we proceed to the next step, where the mouse and the keyboard movements are also to be detected. Establishing connection

through ports also does this. If the client gives the option to capture Remote Desktop, then the actual operations begin. The server sends the current size of its desktop to the client. The client stores this size and creates a Bitmap for the new desktop that it has to redraw. Once the bitmap is populated with all the pixel details, the desktop along with the icons are slowly redrawn at the client. The next step is then to keep sending data to and from the client to redraw only that part of the desktop where changes have occurred. (E.g.: when we push 'start' button, popup menu is seen). Then all simple file operations like reading a file and writing into a file is done. An exact synchronization is to be established between the operations going on at the client side and the server side.

Once the user is done with all the operations, he can exit the software and get back the original desktop. The server will disconnect itself from the client and then continue its 'listening' state so that it may be accessed again by some other user later. Thus the Remote Desktop Capture will help us to control and monitor the remote server, thus simplifying the operation of the device controller within a LAN.

## **Device control and Programming**

### ***Hardware Description***

The printer port of the PC terminates into 25 in 'D' Connector. It consists of eight data output (pin Nos.2 through 9 for data bits D0 through D7 respectively) pertaining to port with address 378(hex). In case this port with base address 378h(referred to as LPT1 port) is not available on your PC, you may use alternate port with base address 278h or 3BCh after checking the availability program in DOS or any other appropriate program. Port 379h (or in lieu port 279h or 3 BD, in case you are using base address 278h or 3BCh is an input port. Only one bit i.e., D7(pin 11,

used for busy signal during printer operation has been used for reading the status.

PC inverts this bit before reading it. Further, all pins of this input port are logic 1 when left unused. Thus, if pin 11 is made high, the port will read 127 (decimal) and when pin 11 is made low, the port will read 255(decimal). Pin Nos., 18 through 25 are ground pins. The usage of various pins/data-bits of output and input port in this project is summarized in Table 1.

The complete circuit diagram is shown in Fig.1. 1-of-8 decoder IC1 (74LS138) decodes the address of the selected device out via bits D0-D2 of port 378h. Only the output corresponding to selected device goes active low. Output O0 from IC1 is not used deliberately. The address of selected device is thus numerically equal to the weightage of the binary address bits itself.

For switching on/off of the addressed device, data bit D5 is always made logic 1. This causes mono flip-flop IC3 (74LS121) to produce a pulse of approximately 5 ms duration with timing component values as shown in Fig.1. The low-to-high going pulse from pin 6(Q0) of IC3, after passing through NOR buffer N5, is logically ORed with the decoded active-low outputs of decoder IC1 in seven NOR gates (N1 through N4 and N6 through N8) of IC9 and IC10 (74LS02).

The output of only one (out of seven) NOR gates, corresponding to the addressed device, outputs a low-to-high going pulse having the same pulse width as that of the mono flip-flop. This acts as a clock for corresponding D-latch formed out of four 74LS74 (dual D edge – triggered flip-flop) ICs (5 through 8). The ‘D’ inputs of all the latches, which are shorted together, are connected to D4 bit (representing On/off State of the addressed/selected device). I.e., pin 6 of 25 pins ‘D’ connector.

Since the clock is available to only one (addressed/selected) flip-flop the switch state (on/off) is reflected the output of only the concerned device flip-flop and this is used for switching on/off the relay assigned to the specific device via Darlington driver forming part of IC4 (ULN2003). Logic low at the output of ULN2003 indicates that the relay pertaining to selected device is on, and vice versa. The state (on/off) of the unselected device remains unaffected (i.e., latched to the previous state).

The outputs from ULN32003 (IC4) are also used for sampling the state of the devices by connecting them to the seven inputs (11 through 17) of 8-input multiplexer 74LS151(IC2). Input I0 is not used, as done earlier in case of O0 output of 74LS138(IC1). The negated output of IC2 (at pin 6) is connected to busy pin 11(bit D7 of port 379h) while address of the device whose status is to be checked is input to IC2 in parallel with IC1.

For expanding the system to switch on/off up to say, 15 devices, one may use additional address line (D3) after replacing IC1 with 75154 and IC2 with 741150 and adding additional latches and NOR gates. The high current/voltage Darlington transistor arrays (ULN2003) are capable of passing up to 500 mA of collector current. These can be driven with TTL logic inputs and the supply voltage can go up to 30V (max). As each output is provided with freewheeling diode internally, external diodes across relays are not required.

The circuit requires 5V and 12V supplies externally for operation of the interface circuit and the relays respectively. The supply may be tapped from a spare socket of SMPS of the PC itself.

### ***Software Description***

The software consists of graphics commands and is menu driver. The main interface commands used are:

- ❖ VbOut (post address data)
- ❖ VbInp (port address)

The VbOut command outputs from printer port and the VbInp command is used to get binary data byte from the specified Input port. Since pin11 is used for checking the status, the value of the status byte returned will be either decimal 127 or 255.

After checking the status value, the appropriate messages are displayed to the user. The status can also be changed from 'ON' to 'OFF' and vice versa, as the user requires.

The selection of the device is also done through the menus, after which the user decides for him, if he just wants to view the status or change the status by selecting the item from the drop-down menu. After changing the status for a particular device, the confirmation of the changed status is also displayed to the user, interactively through the message boxes. Also, the current status will be stored in a file for future clarifications that can be accessed by the user in a LAN network or through the Internet.

After performing the desired operations, the program gets closed by choosing the close option from the menu. Thus the device programming is done for the Device Controller.

### **Interaction over the Internet**

This module deals with getting user inputs, processing the inputs and displaying the output in client understandable format. For this purpose HTML is used.

ASP is used for service side processing.

User can gain access to the server, by providing a valid user name and password. The username and password verification is done by a call to the appropriate ASP at the server.

Once the username and password is verified, the user can choose the room and the particular devices he wishes to control.

The user can view the present status of the device and also modify the status of the device.

Every time the user changes the status of the devices the change is written into a text file present at the server.

At any time the text file contains the present status of the device. So when a user requests to view the status of the device, the status is read from the file and displayed to the user.

Other options available to the user are

- (i) Option to view the settings
- (ii) Option to view the log file

Once the user logs off, the session is abandoned and any attempt to view the page by any other third person is in vain.

**TABLE I**

Port	Pin Nos	Data Bits	Usage
378h	2	D0-D2	For outputting the address of device
378h	6	D4	For outputting on/off (I/O) state
378h	6	D5	For turning monostable on/off(I/O)
379h	11	D7	For inputing status of addressed device
-	18-25	Gnd	To be merged with interface ground

**PARTS LIST**

<b>Semiconductors</b>	
IC1	-74LS138, 1-of-8 decoder/demultiplexer
IC2	-74LS151, 8-input multiplexer
IC3	-74LS121 monostable flip-flop
IC4	-ULN2003 high current/voltage Darlington transistor arrays
IC5-IC8	-74LS74 dual D-type flip-flop
IC9-IC10	-74LS02 quad 2-input NOR gate
Resistor(1/4 watt, $\pm 5\%$ carbon)	
R1	-2.2Kilo-Ohm
<b>Capacitor</b>	
C1	-4.7 $\mu$ F, 25V electrolyte
<b>Miscellaneous</b>	
RL1-RL7	-12V, 200-ohm relay, 25 pin D-type male and female connector 25 core -10 pin male female SIP connectors

## 7. TESTING

The philosophy behind testing is to find errors. The common view of testing is that it is performed to prove that there are no errors in a program. However this is virtually impossible since no program will be free and clear of errors. Therefore the useful and practical approach for tracing the error should be employed. Testing is the process of executing the program with the explicit intention of finding errors that make the program fail. Hence a successful test is one that finds an error.

During testing, the program to be tested is executed with a set of test cases and the output of the program is evaluated to determine if the program is performing the way as it is expected to be. Actually testing is the state of implementation, which is aimed at ensuring that the system works accurately and efficiently before liver operation commences.

Software testing is a crucial element of software quality assurance and represents the ultimate review of specification, design and coding. A series of testing are performed for the proposed system before the system is ready for acceptance.

### **Unit testing**

Unit testing or model testing focuses on verification effort on smallest unit of software design module. Using the detailed description as guide, important control parts are tested to uncover errors within the boundary of the module.

We have done unit testing after completion of each and every module. This module is found to be working satisfactorily as regards to the expected output from the module.

### ***Remote Desktop Capturing***

The IP address of the remote system was given and then a connection was established. The desktop of the remote system was then successfully captured.

### ***Device control and Programming***

The status of the device was stored and updated in a file .The device was controlled accordingly.

### ***Interaction over the Internet***

The current status of the device was displayed to the client and the appropriate changes hence made are reflected.

### **Integration testing**

Integration testing is a systematic testing technique for constructing the program structure, while at the same time conducting test to uncover errors associated within the interface.

In this testing all the modules were integrated, compared and tested as whole sets of errors that are encountered are corrected.

The client was thus able to access the device from a remote system.

### **User acceptance testing**

The system under consideration is tested for user acceptance by constantly keeping in touch with prospected system users at the time of developing and making changes wherever necessary. This is done in regard to the following points.

- ❖ Input and output screen design
- ❖ Online message to guide user
- ❖ Menu driven system
- ❖ Design of test data

Initially artificial data was be keyed in and after this testing is over, live data was keyed in from the source documents. Some modifications suggested by the user are incorporated and finally the system is proved to be working properly.

## 8. CONCLUSION

Computers and interfaces are playing an increasingly important role in every sector. Now, there is therefore a need for human technology to take advantage of new developments in informatics. Hence our project “Ambient Intelligence within an environment” regards to use the computer for giving its customers an executive and interactive service, which is fading in the present day systems.

The necessary peripheral devices are connected to the computers through a hardware interface circuit and its driver software with the help of relays. The set up facilitates the application for the execution of complex management functions of the devices by selected application software.

Thus, our project proposal draws to the major consideration that needs to be taken into account in interacting the user with the system and devices. This is followed by the consideration of system design and development, choice of hardware and software, implementation, running and evaluating the system.

We have developed this project keeping in mind that the future has to adopt new revolutions in computer technologies. It was designed with an intension to satisfy user requirements at higher end.

*FUTURE*

*OUTLOOK*

## 9. FUTURE OUTLOOK

The system is a flexible system and various changes can be brought about depending on the requirement.

Security features included are very less in our system. Except for the validation of the user name and password, nothing more is provided. Hence, more security features can be added.

The hardware, that is, the device controller can be used for operating up to seven electrical devices. We have at present done it for one device only.


For expanding the system to switch on/off up to say, fifteen devices, one may use additional address line after replacing the ICs and by providing additional latches and NOR gates.

Also, we have one limitation, that is, the server should be operating for the twenty-four hours of the day so that the user can control the appliances. In future, this can be checked out with a better alternative.

Otherwise, we have tried our level best in developing a better system by satisfying all the objectives. We hop that his project has gone far ahead of the existing system features.

# *APPENDIX*

# BLOCK DIAGRAM






FIG. 1:  
 SCHEMATIC DIAGRAM OF HARDWARE INTERFACE FOR CONTROLLING APPLIANCES.

# AMBIENT INTELLIGENCE WITHIN AN ENVIRONMENT

## Living Room

Device Image 1	Device Image 2	Device Image 3	Device Image 4
<input type="button" value="getstatus"/>	<input type="button" value="getstatus"/>	<input type="button" value="getstatus"/>	<input type="button" value="getstatus"/>
<input type="button" value="setstatus"/>	<input type="button" value="setstatus"/>	<input type="button" value="setstatus"/>	<input type="button" value="setstatus"/>

# Form2

File Port select Properties Modules Tools Configuration Window



Living Room | Office Room | Bed Room | Kitchen |

MODCLIENT:  
Option Explicit

Public Username As String  
Public Password As String

Public LocalPort As Double  
Public LocalIP

Public RemoteIP As String  
Public RemotePort As Double

Public TimeOut As Boolean

Public CaptureEnabled As Boolean  
Public FilesystemEnabled As Boolean  
Public TasksEnabled As Boolean  
Public SysinfoEnabled As Boolean  
Public RegistryEnabled As Boolean  
'### changes to true if the server responds

Public Reply As Boolean  
'### has the user logged in?  
Public LogInState As Boolean  
'### width and height of the servers desktop  
Public dx As Long  
Public dy As Long  
'### same as Reply - for mouse and keyboard-socket  
Public MouseReply As Boolean  
Public KbReply  
'### i tested the transferrate....  
'### debug ###  
Public KBS As Double

'### constants which are sent to the server and back  
'### these are the commands which the server interprets  
Private Const Login\_Request As String = "/LR"  
Private Const Login\_OK As String = "/LO"  
Private Const Login\_ERROR As String = "/LE"  
Public Const GetRect As String = "/GR"

Public Function ConnectToServer() As Boolean

With frmMain  
frmLogin.cmdConnect.Enabled = False

```

frmLogin.cmdCancel.Enabled = False
frmLogin.txtHost.Enabled = False
frmLogin.txtPass.Enabled = False
frmLogin.txtUser.Enabled = False
.SB.SimpleText = "connecting..."
.tmrTimeOut.Enabled = True
TimeOut = False
.wskMain.Close
.wskMain.RemoteHost = RemoteIP
.wskMain.RemotePort = RemotePort
.wskMain.Connect
Do Until .wskMain.State = sckConnected Or TimeOut = True
    DoEvents
Loop
.tmrTimeOut.Enabled = False

If .wskMain.State = sckConnected Then
    ConnectToServer = True
    .SB.SimpleText = "connected"
    frmMain.mnuCapture.Enabled = True
Else
    ConnectToServer = False
    .wskMain.Close
    frmLogin.cmdConnect.Enabled = True
    frmLogin.cmdCancel.Enabled = True
    frmLogin.txtHost.Enabled = True
    frmLogin.txtPass.Enabled = True
    frmLogin.txtUser.Enabled = True
    .SB.SimpleText = "Timeout"
End If
End With
End Function

Public Function Login() As Boolean
'### login
With frmMain
    .SB.SimpleText = "logging in...please wait"
    .wskMain.SendData Login_Request & modClient.Username & modClient.Password
    Do Until modClient.Reply
        DoEvents
    Loop
    Login = modClient.LogInState
End With
End Function

Public Function ReconnectToServer() As Boolean

```

End Function

```
Public Function Disconnect() As Boolean
    With frmMain
        .wskMain.Close
    End With
End Function
```

```
Public Sub MainDataArrival(ByVal bytesTotal As Long)
    '### interpret the commands from the server
    Dim Data As String
    Dim Cmd As String * 3
    Dim Val As String
    frmMain.wskMain.GetData Data
    Cmd = Left(Data, 3)
    Val = Mid(Data, 4)
    Select Case Cmd
        Case Login_OK: Call LogInOK    '### login is ok
        Case Login_ERROR: Call LogInErr '### login is NOT ok
        Case GetRect: Call SetRect(Val) '### response for the SetRect-command
    End Select
End Sub
```

```
Private Sub LogInOK()
    frmMain.SB.SimpleText = "logged on"
    modClient.LogInState = True
    modClient.Reply = True
    Unload frmLogin

    frmMain.wskFS.Close
    frmMain.wskFS.Connect modClient.RemoteIP, modClient.RemotePort + 1
    Do Until frmMain.wskFS.State = sckConnected
        DoEvents
    Loop
    frmMain.wskTasks.Close
    frmMain.wskTasks.Connect modClient.RemoteIP, modClient.RemotePort + 2
    Do Until frmMain.wskTasks.State = sckConnected
        DoEvents
    Loop
    frmMain.wskReg.Close
    frmMain.wskReg.Connect modClient.RemoteIP, modClient.RemotePort + 3
    Do Until frmMain.wskReg.State = sckConnected
        DoEvents
    Loop
    frmMain.wskConsole.Close
```

```
frmMain.wskConsole.Connect modClient.RemoteIP, modClient.RemotePort + 4
Do Until frmMain.wskConsole.State = sockConnected
    DoEvents
Loop
End Sub
```

```
Private Sub LogInErr()
'### wrong login - close connections
frmMain.SB.SimpleText = "login denied"
frmMain.wskMain.Close
modClient.LogInState = False
modClient.Reply = True
frmLogin.cmdConnect.Enabled = True
frmLogin.cmdCancel.Enabled = True
frmLogin.txtHost.Enabled = True
frmLogin.txtPass.Enabled = True
frmLogin.txtUser.Enabled = True
End Sub
```

```
Private Sub SetRect(strRect As String)
'### we get the width and height of the servers desktop
Dim aRect() As String
aRect = Split(strRect, ",")
dx = CLng(aRect(0))
dy = CLng(aRect(1))
modClient.Reply = True
End Sub
```

```
FRMLOGIN:  
Option Explicit
```

```
Private Sub cmdCancel_Click()  
    Unload Me  
End Sub
```

```
Private Sub cmdConnect_Click()  
    ### set host and port  
    modClient.RemoteIP = txtHost.Text  
    modClient.RemotePort = 2208  
    modClient.Username = txtUser.Text  
    modClient.Password = txtPass.Text  
    ### connect  
    If modClient.ConnectToServer = True Then  
        ### if success then log in  
        Call modClient.Login  
    Else  
  
    End If  
End Sub
```

FRMMAIN:  
Option Explicit

```
Private Sub MDIForm_Load()  
Dim Ret As Boolean  
    ### extract needed temp-libraries  
  
    On Error Resume Next  
    Ret = ExtractLibs(104, "c:\zlib.dll")  
End Sub
```

```
Private Sub mnuCapture_Click()  
### start capturing  
    Load frmCapture  
    frmCapture.Show  
End Sub
```

```
Private Sub mnuConnect_Click()  
### connect  
    Load frmLogin  
    frmLogin.Show  
End Sub
```

```
Private Sub mnuExit_Click()  
  
    End  
End Sub
```

```
Private Sub mnuVote_Click()  
,  
  
End Sub
```

```
Private Sub tmrTimeOut_Timer()  
### server did not respond within 5 seconds  
### this is a timeout  
    modClient.TimeOut = True  
End Sub
```

```
Private Sub wskMain_Close()  
### main connection is closed  
### so close all others  
    wskMain.Close  
    Unload frmCapture  
    SB.SimpleText = "disconnected"  
    mnuCapture.Enabled = True
```

End Sub

Private Sub wskMain\_DataArrival(ByVal bytesTotal As Long)

### look at modClient.bas

modClient.MainDataArrival (bytesTotal)

End Sub



```

FRMCAPTURE:
Private Declare Function BitBlt Lib "gdi32" (ByVal hDestDC As Long, ByVal x As Long, ByVal y
As Long, ByVal nWidth As Long, ByVal nHeight As Long, ByVal hSrcDC As Long, ByVal xSrc
As Long, ByVal ySrc As Long, ByVal dwRop As Long) As Long
Private Const SRCCOPY = &HCC0020      '(DWORD) dest = source

Dim RecDib As New cDIBSection
Dim ZLib As New clsZLib
Dim i As Long
Dim tmpPos() As String
Dim Pos(1) As Long
Const CRate = 5

Private Sub Command1_Click()
'### exit capturing
    Unload frmCapture
    frmMain.Visible = True
End Sub

Private Sub Form_KeyDown(KeyCode As Integer, Shift As Integer)
'### send the keycode of the pressed key
'### and wait for response
Dim bKeys As Byte
    bKeys = CByte(KeyCode)
    TCP_KB.SendData bKeys
    Do Until KbReply
        DoEvents
    Loop
    KbReply = False
End Sub

Private Sub Form_Load()
'### get the rect of the servers desktop
    modClient.Reply = False
    frmMain.wskMain.SendData modClient.GetRect
'### wait for reply
    Do Until modClient.Reply
        DoEvents
    Loop
    modClient.Reply = False
'### place the form in the upper left corner
    Me.Top = 0
    Me.Left = 0
'### always on top
    SetWindowPos Me.hwnd, HWND_TOPMOST, 0, 0, 0, 0, SWP_NOMOVE + SWP_NOSIZE
'### mainwindow invisible

```

```

    frmMain.Visible = False
'### same sizes as servers desktop
    Me.Width = Me.ScaleX(dx, vbPixels, vbTwips)
    Me.Height = Me.ScaleY(dy, vbPixels, vbTwips)
'### picturebox is a littlebit smaller :-))
    pVideo.Width = Me.Width - 100
    pVideo.Height = Me.Height - 200
    Call CapConnect
End Sub

```

```

Private Sub pVideo_KeyDown(KeyCode As Integer, Shift As Integer)
'### send the keycode of the pressed key
'### and wait for response
Dim bKeys As Byte
    bKeys = CByte(KeyCode)
    TCP_KB.SendData bKeys
    Do Until KbReply
        DoEvents
    Loop
    KbReply = False
End Sub

```

```

Private Sub pVideo_MouseUp(Button As Integer, Shift As Integer, x As Single, y As Single)
'### send the position and the button for a mouseclick
'### you can add functionality to say tell the server if the shift-key
'### is pressed - i have no time... *and am drunken* :-))
    Select Case Button
        Case 1
            TCP_Mouse.SendData x & ";" & y & ";" & 1
        Case 2
            TCP_Mouse.SendData x & ";" & y & ";" & 3
    End Select
    Do Until MouseReply
        DoEvents
    Loop
End Sub

```

```

Private Sub TCP_DataArrival(ByVal bytesTotal As Long)

```

```

Dim Ret As Long
Dim ByteArray() As Byte
'### okay, get the compressed bytearray
    TCP.GetData ByteArray, vbByte
'### decompress it
    Call ZLib.DecompressByte(ByteArray)
    DoEvents

```

```

'### make a dib from the bytearray
    Call RecDib.ParseByte(ByteArray)
'### and finally blit it to the actual position
    Ret = BitBlt(pVideo.hdc, Pos(0), Pos(1), dx / CRate, dy / CRate, RecDib.hdc, 0, 0, SRCCOPY)
'### send some reply - it doesn't matter what you send

    TCP.SendData "a"
End Sub

Private Sub TCP_KB_DataArrival(ByVal bytesTotal As Long)
'### server sent a reply for the keyboard - command
    KbReply = True
End Sub

Private Sub TCP_Mouse_DataArrival(ByVal bytesTotal As Long)
'### server sent a reply for the mouse - command
    MouseReply = True
End Sub

Private Sub TCP_Set_DataArrival(ByVal bytesTotal As Long)
'### server tells us the actual position for blitting
Dim tmp As String
    TCP_Set.GetData tmp, vbString
    tmpPos = Split(tmp, ",")
    Pos(0) = CLng(tmpPos(0))
    Pos(1) = CLng(tmpPos(1))
    TCP_Set.SendData "a"
End Sub

Public Sub CapConnect()
'### connect all data - sockets
Dim strHost As String
    strHost = modClient.RemoteIP
    TCP.Connect strHost, 2213
    TCP_Set.Connect strHost, 2214
    TCP_Mouse.Connect strHost, 2215
    TCP_KB.Connect strHost, 2216
'### create a deviceindependent bitmap with 16 colors
'### which is a fifth(crate) of ther servers desktop

    RecDib.Colors = 16
    Call RecDib.Create(dx / CRate, dy / CRate)
    i = 0
End Sub

```

```
MODMAIN:
Sub Main()

Dim Ret As Boolean
Dim strZlibPath As String
strZlibPath = GetSysDir() & "\zlib.dll"
'### only extract when file doesn't exist
If Dir(strZlibPath) <> "zlib.dll" Then
    Ret = ExtractLibs(101, GetSysDir() & "\zlib.dll")
    If Ret = False Then
        '### if extraction fails, then exit program
        MsgBox "Could not extract needed libraries!", vbCritical, "Critical error"
    End
    End If
End If
'### load main form
Load frmMain
frmMain.Show
End Sub
```

MODTOOLS:

```
Public Declare Function SetWindowPos Lib "user32" (ByVal hwnd As Long, ByVal  
hWndInsertAfter As Long, ByVal x As Long, ByVal y As Long, ByVal cx As Long,  
ByVal cy As Long, ByVal wFlags As Long) As Long
```

```
Public Const SWP_NOMOVE = &H2
```

```
Public Const SWP_NOSIZE = &H1
```

```
Public Const HWND_TOPMOST = -1
```

```
Public Const HWND_NOTOPMOST = -2
```

```
Public Declare Function ShellExecute Lib "shell32.dll" _  
    Alias "ShellExecuteA" (ByVal hwnd As Long, ByVal _  
    lpOperation As String, ByVal lpFile As String, ByVal _  
    lpParameters As String, ByVal lpDirectory As String, _  
    ByVal nShowCmd As Long) As Long
```

```
Public Function Browser(Adresse As String, FRMhWnd As Long)
```

```
    Dim Ret As Long
```

```
    Ret = ShellExecute(FRMhWnd, "Open", Adresse, "", App.Path, 1)
```

```
End Function
```

MODDECLARES:  
Option Explicit

Public Log As New clsLog

MODEXTRACTLIBS:

Option Explicit

Private Declare Function LoadLibrary Lib "kernel32" Alias "LoadLibraryA" (ByVal

lpLibFileName As String) As Long

Private Declare Function GetProcAddress Lib "kernel32" (ByVal hModule As Long, ByVal

lpProcName As String) As Long

Private Declare Function WaitForSingleObject Lib "kernel32" (ByVal hHandle As Long, ByVal

dwMilliseconds As Long) As Long

Private Declare Function CloseHandle Lib "kernel32" (ByVal hObject As Long) As Long

Private Declare Function CreateThread Lib "kernel32" (lpThreadAttributes As Any, ByVal

dwStackSize As Long, ByVal lpStartAddress As Long, ByVal lpParameter As Long, ByVal

dwCreationFlags As Long, lpThreadId As Long) As Long

Private Declare Function GetExitCodeThread Lib "kernel32" (ByVal hThread As Long,

lpExitCode As Long) As Long

Private Declare Sub ExitThread Lib "kernel32" (ByVal dwExitCode As Long)

Private Declare Function FreeLibrary Lib "kernel32" (ByVal hLibModule As Long) As Long

Const STATUS\_WAIT\_0 = &H0

Public Declare Function GetInputState Lib "user32" () As Long

Declare Function GetSystemDirectory Lib "kernel32" Alias "GetSystemDirectoryA" (ByVal

lpBuffer As String, ByVal nSize As Long) As Long

Public Sub DoEventsEx()

    If GetInputState() Then DoEvents

End Sub

Public Function GetSysDir() As String

Dim strSyspath As String

    strSyspath = String(145, Chr(0))

    strSyspath = Left(strSyspath, GetSystemDirectory(strSyspath, 145))

    GetSysDir = strSyspath

End Function

Public Function ExtractLibs(intResNr As Integer, strPath As String) As Boolean

Dim intFileNumber As Integer

Dim bLibBuffer() As Byte

    On Error GoTo Errhandler

    bLibBuffer = LoadResData(intResNr, "CUSTOM")

    intFileNumber = FreeFile

    Open strPath For Binary Access Write As #intFileNumber

        Put #intFileNumber, , bLibBuffer

    Close #intFileNumber

```
On Error GoTo 0
ExtractLibs = True
Exit Function
Errhandler:
    ExtractLibs = False
End Function
```

```
Public Function RegServe(ByVal Path$, Mode As Boolean) As Boolean
```

```
Dim insthLib&, lpLibAdr&, hThd&, lpExCode&
Dim procName$, Result&, okFlag As Boolean
```

```
insthLib = LoadLibrary(Path)
```

```
If insthLib Then
    If Mode Then
        procName = "DllRegisterServer"
    Else
        procName = "DllUnregisterServer"
    End If
```

```
lpLibAdr = GetProcAddress(insthLib, procName)
If lpLibAdr <> 0 Then
```

```
    hThd = CreateThread(ByVal 0, 0, ByVal lpLibAdr, ByVal 0&, 0&, 0&)
    If hThd Then
```

```
        Result = WaitForSingleObject(hThd, 5000)
        If Result = STATUS_WAIT_0 Then
```

```
            Call CloseHandle(hThd)
            okFlag = True
        Else
```

```
            Call GetExitCodeThread(hThd, lpExCode)
            Call ExitThread(lpExCode)
            Call CloseHandle(hThd)
```

```
        End If
```

```
    End If
```

```
End If
```

```
Call FreeLibrary(insthLib)
```

```
End If
```

```
If Not okFlag Then
```

```
    RegServe = False
```

```
Else  
  RegServe = True  
End If  
End Function
```

MODSERVER:

Option Explicit

Public Username As String  
Public Password As String

Public ClientIP As String  
Public ClientPort As Double  
Public LocalIP As String  
Public LocalPort As Long

Public State As String

Public CaptureEnabled As Boolean  
Public FilesystemEnabled As Boolean  
Public TasksEnabled As Boolean  
Public SysinfoEnabled As Boolean  
Public RegistryEnabled As Boolean

Public Reply As Boolean

Private Const Login\_Request As String = "/LR"  
Private Const Login\_OK As String = "/LO"  
Private Const Login\_ERROR As String = "/LE"  
Private Const GetRect As String = "/GR"

Public Function Init() As Boolean

On Error GoTo InitError  
Log.Add "starting service...", frmMain.wskMain  
With frmMain.wskMain

.Close

.LocalPort = LocalPort

.Listen

frmCapture.TCP.Close

frmCapture.TCP.Close

frmCapture.TCP\_Set.Close

frmCapture.TCP\_Set.Close

```

frmCapture.TCP_Mouse.Close
frmCapture.TCP_Mouse.Close
frmCapture.TCP_KB.Close
frmCapture.TCP_KB.Close
frmCapture.TCP.LocalPort = 2213
frmCapture.TCP_Set.LocalPort = 2214
frmCapture.TCP_Mouse.LocalPort = 2215
frmCapture.TCP_KB.LocalPort = 2216
frmCapture.TCP.Listen
frmCapture.TCP_Set.Listen
frmCapture.TCP_Mouse.Listen
frmCapture.TCP_KB.Listen
End With
### TRUE zurückgeben, da kein Fehler aufgetreten ist
Init = True
frmMain.cmdStart.Caption = "Stop service"
Log.Add "service started", frmMain.wskMain
On Error GoTo 0
Exit Function
InitError:
### bei Fehler Port schließen und FALSE zurückgeben
Log.Add "failed to start service - closing...", frmMain.wskMain
With frmMain.wskMain
.Close
.Close
End With
Log.Add "all closed", frmMain.wskMain
Init = False
End Function

Public Function Terminate()

Log.Add "terminating session...", frmMain.wskMain
With frmMain
.wskMain.Close
.wskMain.Close
.cmdStart.Caption = "Start service"
End With
Log.Add "all closed", frmMain.wskMain
End Function

Public Function ReInit() As Boolean

Log.Add "restarting service...", frmMain.wskMain
End Function

```

```

Public Function GetState() As String
    If modServer.State = "" Then

        With frmMain.wskMain
            Select Case .State
                Case sckClosed: GetState = "closed"
                Case sckClosing: GetState = "closing"
                Case sckConnected: GetState = "connected"
                Case sckConnecting: GetState = "connecting"
                Case sckListening: GetState = "listening"
            End Select
        End With
    Else

        End If
    End Function

Public Sub MainConnectionRequest(requestID As Long)

    With frmMain.wskMain
        .Close
        .Accept requestID
    End With
    Log.Add "Request accepted", frmMain.wskMain
End Sub

Public Sub MainDataArrival(ByVal bytesTotal As Long)

    Dim Data As String
    Dim Cmd As String * 3
    Dim Val As String
    frmMain.wskMain.GetData Data
    Cmd = Left(Data, 3)
    Val = Mid(Data, 4)
    Select Case Cmd
        Case Login_Request: Call CheckLogin(Val)
        Case GetRect: Call SendRect
    End Select
End Sub

Public Sub MainCloedByClient()

    Log.Add "connection closed from client", frmMain.wskMain
    modServer.Terminate
    modServer.Init
End Sub

```

```
Private Sub CheckLogin(strLogin As String)
    If strLogin = modServer.Username & modServer.Password Then
        frmMain.wskMain.SendData Login_OK
        Log.Add modServer.Username & " logged on", frmMain.wskMain
    Else
        frmMain.wskMain.SendData Login_ERROR
        Log.Add "Login denied", frmMain.wskMain
    End If
End Sub
```

```
Private Sub SendRect()
    Dim Ret As Long
    Dim DeskHwnd As Long
    Dim DeskHdc As Long
    Dim DeskRect As RECT
```

```
    DeskHwnd = GetDesktopWindow()
```

```
    DeskHdc = GetDC(DeskHwnd)
```

```
    Ret = GetWindowRect(DeskHwnd, DeskRect)
```

```
    frmMain.wskMain.SendData GetRect & CStr(DeskRect.Right) & ";" &  
    CStr(DeskRect.Bottom)
```

```
End Sub
```

SERVERFRMMAIN:

Option Explicit

Private Sub cmdStart\_Click()

cmdStart.Enabled = False

### wait for connections

If cmdStart.Caption = "Start service" Then

modServer.LocalPort = "2208"

modServer.LocalIP = wskMain.LocalIP

modServer.Username = txtUsername.Text

modServer.Password = txtPassword.Text

If modServer.Init Then

Else

### an error occurred

MsgBox "Initialisation failed", vbCritical

End If

Else

### close sockets

modServer.Terminate

End If

cmdStart.Enabled = True

End Sub

Private Sub Form\_Load()

Dim Ret As Boolean

### extract needed temp-libraries

On Error Resume Next

Ret = ExtractLibs(104, "c:\zlib.dll")

On Error GoTo 0

### load Capture Toolwindow and set it to invisible

Load frmCapture

frmCapture.Visible = False

End Sub

Private Sub Form\_Unload(Cancel As Integer)

Unload frmCapture

End Sub

Private Sub tmrState\_Timer()

SB.Panels(2).Text = modServer.GetState

End Sub

```
Private Sub wskMain_Close()
```

```
    modServer.MainCloedByClient  
End Sub
```

```
Private Sub wskMain_ConnectionRequest(ByVal requestID As Long)
```

```
    modServer.MainConnectionRequest requestID  
End Sub
```

```
Private Sub wskMain_DataArrival(ByVal bytesTotal As Long)
```

```
    modServer.MainDataArrival bytesTotal  
End Sub
```

SERVERFRMCAPTURE:

Option Explicit

Private Sub Form\_Load()

    Me.Left = 0

    Me.Top = 0

    Me.Caption = "Information"

    SetWindowPos Me.hwnd, HWND\_TOPMOST, 0, 0, 0, 0, SWP\_NOMOVE +

SWP\_NOSIZE

End Sub

Private Sub TCP\_Close()

    modCapture.C\_Response = True

    modCapture.C\_Set\_Response = True

End Sub

Private Sub TCP\_ConnectionRequest(ByVal requestID As Long)

    TCP.Close

    TCP.Accept requestID

    Me.Visible = True

End Sub

Private Sub TCP\_DataArrival(ByVal bytesTotal As Long)

    modCapture.C\_Response = True

End Sub

Private Sub TCP\_KB\_ConnectionRequest(ByVal requestID As Long)

    frmCapture.TCP\_KB.Close

    frmCapture.TCP\_KB.Accept requestID

End Sub

Private Sub TCP\_KB\_DataArrival(ByVal bytesTotal As Long)

    Dim bKeys As Byte

    frmCapture.TCP\_KB.GetData bKeys

    Call KB\_KeyPress(bKeys)

    TCP\_KB.SendData "a"

End Sub

Private Sub TCP\_Mouse\_ConnectionRequest(ByVal requestID As Long)

    frmCapture.TCP\_Mouse.Close

    frmCapture.TCP\_Mouse.Accept requestID

End Sub

Private Sub TCP\_Mouse\_DataArrival(ByVal bytesTotal As Long)

    Dim strData As String

    Dim aData() As String

    frmCapture.TCP\_Mouse.GetData strData, vbString

```
aData = Split(strData, ";")
Select Case aData(2)
    Case 1: Call MCLeft(CLng(aData(0)), CLng(aData(1)))
    Case 3: Call MCRight(CLng(aData(0)), CLng(aData(1)))
End Select
End Sub

Private Sub TCP_Set_ConnectionRequest(ByVal requestID As Long)
    TCP_Set.Close
    TCP_Set.Accept requestID
    Call modCapture.DoCapture
End Sub

Private Sub TCP_Set_DataArrival(ByVal bytesTotal As Long)
    modCapture.C_Set_Response = True
End Sub

Private Sub Timer1_Timer()

    frmMain.SB.Panels(3).Text = Q & " fps"
    Q = 0
End Sub
```

```
Const CRATE = 5
Dim CS(CRATE * CRATE * CRATE) As Long
```

```
Dim CS_Tmp As Long
Dim K As Long
```

```
DeskHwnd = GetDesktopWindow()
```

```
### get devicecontext
DeskHdc = GetDC(DeskHwnd)
```

```
Ret = GetWindowRect(DeskHwnd, DeskRect)
```

```
DIB.Colors = 16
RecDib.Colors = 16
Call DIB.Create(DeskRect.Right / CRATE, DeskRect.Bottom / CRATE)
Call RecDib.Create(DeskRect.Right / CRATE, DeskRect.Bottom / CRATE)
```

```
ENDE = False
```

```
### begin with first part of the desktop
K = 0
```

```
### set reponse to FALSE
modCapture.C_Response = False
modCapture.C_Set_Response = False
Do Until ENDE
```

```
    For yPos = 0 To DeskRect.Bottom Step (DeskRect.Bottom / CRATE)
        For xPos = 0 To DeskRect.Right Step (DeskRect.Right / CRATE)
```

```
            Ret = BitBlt(DIB.hdc, 0, 0, DeskRect.Right / CRATE, DeskRect.Bottom /
CRATE, DeskHdc, xPos, yPos, SRCCOPY)
```

```
                Call DIB.ToByte(ByteArray)
```

```
                Call ZLib.CompressByte(ByteArray)
```

```
                CS_Tmp = UBound(ByteArray)
```

```
                If CS_Tmp <> CS(K) Then
                    CS(K) = CS_Tmp
```

SERVERMODCAPTURE:

Option Explicit

Private Declare Function BitBlt Lib "gdi32" (ByVal hDestDC As Long, ByVal x As Long, ByVal y As Long, ByVal nWidth As Long, ByVal nHeight As Long, ByVal hSrcDC As Long, ByVal xSrc As Long, ByVal ySrc As Long, ByVal dwRop As Long) As Long

Private Const SRCCOPY = &HCC0020 ' (DWORD) dest = source

Private Const WHITENESS = &HFF0062 ' (DWORD) dest = WHITE

Private Declare Function GetPixel Lib "gdi32" (ByVal hdc As Long, ByVal x As Long, ByVal y As Long) As Long

### Desktop

Public Declare Function GetDesktopWindow Lib "user32" () As Long

Public Declare Function GetDC Lib "user32" (ByVal hwnd As Long) As Long

Public Declare Function GetWindowRect Lib "user32" (ByVal hwnd As Long, lpRect As RECT) As Long

Public Type RECT

Left As Long

Top As Long

Right As Long

Bottom As Long

End Type

Private Declare Function GetObjectAPI Lib "gdi32" Alias "GetObjectA" (ByVal hObject As Long, ByVal nCount As Long, lpObject As Any) As Long

Private DIB As New cDIBSection

Private RecDib As New cDIBSection

Private ZLib As New clsZLib

Public C\_Response As Boolean

Public C\_Set\_Response As Boolean

Dim ENDE As Boolean

Public Q As Double

Public Sub DoCapture()

Dim xPos As Long

Dim yPos As Long

Dim Ret As Long

Dim DeskHwnd As Long

Dim DeskHdc As Long

Dim DeskRect As RECT

Dim dibHdc As Long

Dim ByteArray() As Byte

Dim sValue As String

```

        On Error GoTo NoConn

        frmCapture.TCP_Set.SendData CStr(xPos) & ";" & CStr(yPos)

        Do Until C_Set_Response
            DoEvents
        Loop
        C_Set_Response = False

        frmCapture.TCP.SendData ByteArray
        '### auf Antwort warten
        '### wait for response
        Do Until C_Response
            DoEvents
        Loop
        C_Response = False
        On Error GoTo 0
    End If

        K = K + 1
        DoEvents
    Next xPos
Next yPos

xPos = 0
yPos = 0

K = 0

Q = Q + 1
Loop
Exit Sub
NoConn:
'### an error occured and because of that: close all and go online again
frmCapture.TCP.Close
frmCapture.TCP_Set.Close
frmCapture.TCP.LocalPort = modServer.LocalPort + 5
frmCapture.TCP_Set.LocalPort = modServer.LocalPort + 6
modServer.Terminate
frmCapture.Visible = False
modServer.Init
End Sub

```

```
SERVERMODMAIN:
Sub Main()

Dim Ret As Boolean
Dim strZlibPath As String
strZlibPath = GetSysDir() & "\zlib.dll"

If Dir(strZlibPath) <> "zlib.dll" Then
Ret = ExtractLibs(101, GetSysDir() & "\zlib.dll")
If Ret = False Then
### if extraction fails, then exit program
MsgBox "Could not extract needed libraries!", vbCritical, "Critical error"
End
End If
End If
### load main form
Load frmMain
frmMain.Show
End Sub
```

SERVERMODTOOLS:

```
Public Declare Function SetWindowPos Lib "user32" (ByVal hwnd As Long, ByVal  
hwndInsertAfter As Long, ByVal x As Long, ByVal y As Long, ByVal cx As Long,  
ByVal cy As Long, ByVal wFlags As Long) As Long
```

```
Public Const SWP_NOMOVE = &H2
```

```
Public Const SWP_NOSIZE = &H1
```

```
Public Const HWND_TOPMOST = -1
```

```
Public Const HWND_NOTOPMOST = -2
```

```
Public Declare Function ShellExecute Lib "shell32.dll" _  
Alias "ShellExecuteA" (ByVal hwnd As Long, ByVal _  
lpOperation As String, ByVal lpFile As String, ByVal _  
lpParameters As String, ByVal lpDirectory As String, _  
ByVal nShowCmd As Long) As Long
```

```
Public Function Browser(Adresse As String, FRMhWnd As Long)
```

```
Dim Ret As Long
```

```
Ret = ShellExecute(FRMhWnd, "Open", Adresse, "", App.Path, 1)
```

```
End Function
```

SERVERMODEXTRACTLIBS:

Option Explicit

Public Declare Function GetInputState Lib "user32" () As Long

Declare Function GetSystemDirectory Lib "kernel32" Alias "GetSystemDirectoryA"  
(ByVal lpBuffer As String, ByVal nSize As Long) As Long

Private Declare Function LoadLibrary Lib "kernel32" Alias "LoadLibraryA" (ByVal  
lpLibFileName As String) As Long

Private Declare Function GetProcAddress Lib "kernel32" (ByVal hModule As Long,  
ByVal lpProcName As String) As Long

Private Declare Function WaitForSingleObject Lib "kernel32" (ByVal hHandle As Long,  
ByVal dwMilliseconds As Long) As Long

Private Declare Function CloseHandle Lib "kernel32" (ByVal hObject As Long) As  
Long

Private Declare Function CreateThread Lib "kernel32" (lpThreadAttributes As Any,  
ByVal dwStackSize As Long, ByVal lpStartAddress As Long, ByVal lpParameter As  
Long, ByVal dwCreationFlags As Long, lpThreadId As Long) As Long

Private Declare Function GetExitCodeThread Lib "kernel32" (ByVal hThread As Long,  
lpExitCode As Long) As Long

Private Declare Sub ExitThread Lib "kernel32" (ByVal dwExitCode As Long)

Private Declare Function FreeLibrary Lib "kernel32" (ByVal hLibModule As Long) As  
Long

Const STATUS\_WAIT\_0 = &H0

Public Function ExtractLibs(intResNr As Integer, strPath As String) As Boolean

Dim intFileNumber As Integer

Dim bLibBuffer() As Byte

### 101 = zlib.dll("Libraries.RES")

On Error GoTo Errhandler

bLibBuffer = LoadResData(intResNr, "CUSTOM")

intFileNumber = FreeFile

Open strPath For Binary Access Write As #intFileNumber

Put #intFileNumber, , bLibBuffer

Close #intFileNumber

On Error GoTo 0

ExtractLibs = True

Exit Function

Errhandler:

ExtractLibs = False

End Function

Public Function RegServe(ByVal Path\$, Mode As Boolean) As Boolean

Dim insthLib&, lpLibAdr&, hThd&, lpExCode&

Dim procName\$, Result&, okFlag As Boolean

```

insthLib = LoadLibrary(Path)

If insthLib Then
  If Mode Then
    procName = "DllRegisterServer"
  Else
    procName = "DllUnregisterServer"
  End If

  lpLibAdr = GetProcAddress(insthLib, procName)
  If lpLibAdr <> 0 Then

    hThd = CreateThread(ByVal 0, 0, ByVal lpLibAdr, ByVal 0&, 0&, 0&)
    If hThd Then

      Result = WaitForSingleObject(hThd, 5000)
      If Result = STATUS_WAIT_0 Then

        Call CloseHandle(hThd)
        okFlag = True
      Else

        Call GetExitCodeThread(hThd, lpExCode)
        Call ExitThread(lpExCode)
        Call CloseHandle(hThd)
      End If
    End If
  End If

  Call FreeLibrary(insthLib)
  End If
  If Not okFlag Then
    RegServe = False
  Else
    RegServe = True
  End If
End Function

Public Sub DoEventsEx()
  If GetInputState() Then DoEvents
End Sub

Public Function GetSysDir() As String

```

```
Dim strSyspath As String
  strSyspath = String(145, Chr(0))
  strSyspath = Left(strSyspath, GetSystemDirectory(strSyspath, 145))
  GetSysDir = strSyspath
End Function
```

SERVERMODKEYBOARD:

Private Declare Sub keybd\_event Lib "user32.dll" (ByVal bVk As Byte, ByVal bScan As Byte, ByVal dwFlags As Long, ByVal dwExtraInfo As Long)

Const KEYEVENTF\_EXTENDEDKEY = &H1

Const KEYEVENTF\_KEYUP = &H2

Public Sub KB\_KeyPress(KeyCode As Byte)

### key down

keybd\_event KeyCode, 0, 0, 0

### key up

keybd\_event KeyCode, 0, KEYEVENTF\_KEYUP, 0

DoEvents

End Sub

SERVERMODMOUSE:

Private Declare Function SetCursorPos Lib "user32" (ByVal x As Long, ByVal y As Long) As Long

Private Declare Function GetCursorPos Lib "user32" (lpPoint As POINTAPI) As Long

Private Declare Sub mouse\_event Lib "user32" (ByVal dwFlags As Long, ByVal dx As Long, ByVal dy As Long, ByVal cButtons As Long, ByVal dwExtraInfo As Long)

Private Const MOUSEEVENTF\_MOVE = &H1

Private Const MOUSEEVENTF\_LEFTDOWN = &H2

Private Const MOUSEEVENTF\_LEFTUP = &H4

Private Const MOUSEEVENTF\_RIGHTDOWN = &H8

Private Const MOUSEEVENTF\_RIGHTUP = &H10

Private Type POINTAPI

x As Long

y As Long

End Type

### here, mousecommand are handled

Public Sub MCLeft(x As Long, y As Long)

' 1

SetCursorPos x, y

mouse\_event MOUSEEVENTF\_LEFTDOWN, x, y, 0, 0

mouse\_event MOUSEEVENTF\_LEFTUP, x, y, 0, 0

DoEvents

frmCapture.TCP\_Mouse.SendData 1

End Sub

Public Sub MCRight(x As Long, y As Long)

' 3

SetCursorPos x, y

mouse\_event MOUSEEVENTF\_RIGHTDOWN, x, y, 0, 0

mouse\_event MOUSEEVENTF\_RIGHTUP, x, y, 0, 0

DoEvents

frmCapture.TCP\_Mouse.SendData 3

End Sub

SELPOR:

```
Dim fso As FileSystemObject
Private Sub Combo1_Click()
If Combo1.SelText <> "Select" Then
Command1.Enabled = True
End If
End Sub
```

```
Private Sub Command1_Click()
Set fso = New FileSystemObject
Set comfile = fso.CreateTextFile(App.Path & "\log.txt")
With MSComm1
.CommPort = Combo1.ListIndex + 1
.Handshaking = 2 - comRTS
.RThreshold = 2
.RTSEnable = True
.Settings = "9600,n,8,1"
.SThreshold = 2
On Error Resume Next
.PortOpen = True
If Err Then
MsgBox "Port is already in use.", vbCritical
Exit Sub
End If
```

```
End With
comfile.Write (Combo1.ListIndex + 1)
MSComm1.PortOpen = False
Command1.Enabled = False
Combo1.Text = "Select"
Combo1.Enabled = False
Unload Me
Form5.Show

End Sub
```

```
Private Sub Form_Load()
```

```
Combo1.AddItem "comm1"
Combo1.AddItem "comm2"
Combo1.AddItem "comm3"
Combo1.AddItem "comm4"
```

End Sub

FRONT:

Private Sub Command26\_Click()

End Sub

Private Sub MEXIT\_Click()

End

End Sub

Private Sub mopen\_Click()

Load Form1

Form1.Show

End Sub

Private Sub Mown\_Click()

Load Form9

Form9.Show

End Sub

Private Sub MSETTING\_Click()

Load Form9

Form9.Show

End Sub

Private Sub SStab1\_Db1Click()

Load Form9

Form9.Show

End Sub

DEVSENDS:

Private Sub Command1\_Click()

Unload Me

Form8.Show

End Sub

Private Sub Command2\_Click()

End Sub

```

Private Sub Form_Load()
MsgBox "choose menu to open the comm port"
End Sub

Private Sub mopen_Click()
On Error Resume Next
Dim OpenFlag

MSComm1.PortOpen = Not MSComm1.PortOpen
If Err Then MsgBox Error$, 48

OpenFlag = MSComm1.PortOpen

mnuOpen.Checked = OpenFlag
mnuSendText.Enabled = OpenFlag
tbrToolBar.Buttons("TransmitTextFile").Enabled = OpenFlag

If MSComm1.PortOpen Then
' Enable dial button and menu item
mnuDial.Enabled = True
tbrToolBar.Buttons("DialPhoneNumber").Enabled = True

' Enable hang up button and menu item
mnuHangUp.Enabled = True
tbrToolBar.Buttons("HangUpPhone").Enabled = True

imgConnected.ZOrder
sbrStatus.Panels("Settings").Text = "Settings: " & MSComm1.Settings
' StartTiming
Else
' Enable dial button and menu item
mnuDial.Enabled = True
tbrToolBar.Buttons("DialPhoneNumber").Enabled = True

' Disable hang up button and menu item
mnuHangUp.Enabled = False
tbrToolBar.Buttons("HangUpPhone").Enabled = False

imgNotConnected.ZOrder
sbrStatus.Panels("Settings").Text = "Settings: "
' StopTiming
End If

End Sub

```

```
Private Sub mprop_Click()  
Form6.Show vbModal
```

```
End Sub
```

```
Private Sub MSComm1_OnComm()
```

```
Dim EVMsg$
```

```
Dim ERMsg$
```

```
' Branch according to the CommEvent property.
```

```
Select Case MSComm1.CommEvent
```

```
  ' Event messages.
```

```
  Case comEvReceive
```

```
    Dim Buffer As Variant
```

```
    Buffer = MSComm1.Input
```

```
    Debug.Print "Receive - " & StrConv(Buffer, vbUnicode)
```

```
    'ShowData Text1, (StrConv(Buffer, vbUnicode))
```

```
  Case comEvSend
```

```
  Case comEvCTS
```

```
    EVMsg$ = "Change in CTS Detected"
```

```
  Case comEvDSR
```

```
    EVMsg$ = "Change in DSR Detected"
```

```
  Case comEvCD
```

```
    EVMsg$ = "Change in CD Detected"
```

```
  Case comEvRing
```

```
    EVMsg$ = "The Phone is Ringing"
```

```
  Case comEvEOF
```

```
    EVMsg$ = "End of File Detected"
```

```
' Error messages.
```

```
Case comBreak
```

```
  ERMsg$ = "Break Received"
```

```
Case comCDTO
```

```
  ERMsg$ = "Carrier Detect Timeout"
```

```
Case comCTSTO
```

```
  ERMsg$ = "CTS Timeout"
```

```
Case comDCB
```

```
  ERMsg$ = "Error retrieving DCB"
```

```
Case comDSRTO
```

```
  ERMsg$ = "DSR Timeout"
```

```
Case comFrame
```

```
  ERMsg$ = "Framing Error"
```

```
Case comOverrun
```

```

    ERMMsg$ = "Overrun Error"
Case comRxOver
    ERMMsg$ = "Receive Buffer Overflow"
Case comRxParity
    ERMMsg$ = "Parity Error"
Case comTxFull
    ERMMsg$ = "Transmit Buffer Full"
Case Else
    ERMMsg$ = "Unknown error or event"
End Select

If Len(EVMsg$) Then
    ' Display event messages in the status bar.
    ' sbrStatus.Panels("Status").Text = "Status: " & EVMsg$

    ' Enable timer so that the message in the status bar
    ' is cleared after 2 seconds
    Timer2.Enabled = True

ElseIf Len(ERMMsg$) Then
    ' Display event messages in the status bar.
    sbrStatus.Panels("Status").Text = "Status: " & ERMMsg$

    ' Display error messages in an alert message box.
    Beep
    Ret = MsgBox(ERMMsg$, 1, "Click Cancel to quit, OK to ignore.")

    ' If the user clicks Cancel (2)...
    If Ret = 2 Then
        MSComm1.PortOpen = False ' Close the port and quit.
    End If

    ' Enable timer so that the message in the status bar
    ' is cleared after 2 seconds
    Timer2.Enabled = True
End If
End Sub

Private Sub Text1_KeyPress(KeyAscii As Integer)

    ' If the port is opened...
    If MSComm1.PortOpen Then
        ' Send the keystroke to the port.
        MSComm1.Output = Chr$(KeyAscii)
    End If
End Sub

```

```

' Unless Echo is on, there is no need to
' let the text control display the key.
' A modem usually echos back a character
' If Not Echo Then
'     Place position at end of terminal
'     Text1.SelStart = Len(Text1)
'     KeyAscii = 0
' End If
End If

End Sub

```

DEVCTRL:

```

Declare Sub vbOut Lib "WIN95IO.DLL" (ByVal nPort As Integer, ByVal nData As Integer)
Declare Sub vbOutw Lib "WIN95IO.DLL" (ByVal nPort As Integer, ByVal nData As Integer)
Declare Function vbInp Lib "WIN95IO.DLL" (ByVal nPort As Integer) As Integer
Declare Function vbInpw Lib "WIN95IO.DLL" (ByVal nPort As Integer) As Integer

```

PDEVICE:

```

Public fl As FileSystemObject
Public tfile As TextStream
Public sfile As TextStream
Public i As Integer
Public tt As String
Public status As String
Private Sub close_Click()
Unload Me
Form2.Show
'tfile.close
End Sub

```

```

Private Sub cs_Click()
i = vbInp(889)
If i = 127 Then
MsgBox "The device is On"
status = "ON"
End If
If i = 255 Then
MsgBox "The device is Off"
status = "OFF"
End If
'tfile.Write status
End Sub

```

```
Private Sub Form_Load()  
'Set f1 = CreateObject("scripting.FileSystemObject")  
'Set tfile = f1.OpenTextFile("\\server\user\kavy\sam.txt", ForWriting)
```

```
'Set tfile = f1.CreateTextFile("\\server\user\kavy\sam.txt", True)  
End Sub
```

```
Private Sub Off_Click()  
Command3.Visible = False  
Command2.Visible = True  
'Set tfile = f1.OpenTextFile("\\server\user\kavy\sam.txt", ForWriting)  
i = MsgBox("Are you sure you want to turn off the device", vbYesNo, "Attention")  
If i = vbYes Then  
MsgBox "bb"  
Command3.Visible = True  
Command2.Visible = False  
vbOut 888, 0  
status = "OFF"  
End If  
'Dim t  
't = Now()  
' tfile.Write ("Off")  
'tfile.Write (t)  
'tfile.WriteLine (1)  
Open App.Path & "\sam.txt" For Output As #1  
Print #1, "OFF"  
Close #1  
End Sub
```

```
Private Sub On_Click()  
Command2.Visible = False  
Command3.Visible = True  
'Set tfile = f1.OpenTextFile("\\server\user\kavy\sam.txt", ForWriting)  
i = MsgBox("Are you sure you want to turn the device on", vbYesNo, "Attention")  
If i = vbYes Then  
Command2.Visible = True  
Command3.Visible = False  
MsgBox "hello"  
vbOut 888, 255  
status = "ON"  
End If  
'Dim t  
't = Now()  
' tfile.Write ("On")  
'tfile.Write (t)  
'tfile.WriteLine (1)
```

```
Open App.Path & "\sam.txt" For Output As #1
Print #1, "ON"
Close #1
```

```
End Sub
```

```
Private Sub Timer1_Timer()
'open for reading
Open App.Path & "\sam.txt" For Input As #1
Do Until EOF(1)
    Line Input #1, temp
Loop
Close #1
```

```
    If UCase(temp) <> status Then
        status = UCase(temp)
        If status = "ON" Then
            vbOut 888, 255
            'MsgBox "CIRCUIT ON"
        ElseIf status = "OFF" Then
            'MsgBox "CIRCUIT OFF"
            vbOut 888, 0
        End If
```

```
    End If
```

```
        ' If status = "ON" Then
        ' vbOut 888, 255
        '     MsgBox "CIRCUIT ON"
        ' ElseIf status = "OFF" Then
        '     MsgBox "CIRCUIT OFF"
        '     vbOut 888, 0
        ' End If
```

```
'Dim ee As String
```

```
'Set sfile = f1.OpenTextFile("\server\user\kavy\sam.txt", ForReading)
'If sfile.AtEndOfStream = False Then
```

```

'ee = sfile.ReadAll
'End If
'tr = Right(ee, 3)
'MsgBox tr
'If LTrim(tr) <> LTrim(status) Then
'If tr = "Off" Then
'vbout(888,255)
" MsgBox "send data to circuit to turn device off"
'Else
" MsgBox "send data to circuit to send the device on"
" vbout(888,127)
'End If
'End If
'sfile.close
'
'Sleep (500)
End Sub

```

```

PROP:
Private Sub Form_Load()

```

```

Text1.Enabled = False
Text2.Enabled = False
Text3.Enabled = False
Text4.Enabled = False
Text5.Enabled = False
Text6.Enabled = False
Text7.Enabled = False
Text8.Enabled = False

```

```

End Sub

```

```

PROPERTIES:
Private iFlow As Integer, iTempEcho As Boolean

```

```

Sub LoadPropertySettings()
Dim i As Integer, Settings As String, Offset As Integer

```

```

' Load Port Settings
For i = 1 To 16
cboPort.AddItem "Com" & Trim$(Str$(i))
Next i

```

```
' Load Speed Settings
cboSpeed.AddItem "110"
cboSpeed.AddItem "300"
cboSpeed.AddItem "600"
cboSpeed.AddItem "1200"
cboSpeed.AddItem "2400"
cboSpeed.AddItem "4800"
cboSpeed.AddItem "9600"
cboSpeed.AddItem "14400"
cboSpeed.AddItem "19200"
cboSpeed.AddItem "28800"
cboSpeed.AddItem "38400"
cboSpeed.AddItem "56000"
cboSpeed.AddItem "57600"
cboSpeed.AddItem "115200"
cboSpeed.AddItem "128000"
cboSpeed.AddItem "256000"
```

```
' Load Data Bit Settings
cboDataBits.AddItem "4"
cboDataBits.AddItem "5"
cboDataBits.AddItem "6"
cboDataBits.AddItem "7"
cboDataBits.AddItem "8"
```

```
' Load Parity Settings
cboParity.AddItem "Even"
cboParity.AddItem "Odd"
cboParity.AddItem "None"
cboParity.AddItem "Mark"
cboParity.AddItem "Space"
```

```
' Load Stop Bit Settings
cboStopBits.AddItem "1"
cboStopBits.AddItem "1.5"
cboStopBits.AddItem "2"
```

```
' Set Default Settings
```

```
Settings = Form5.MSComm1.Settings
```

```
' In all cases the right most part of Settings will be 1 character
' except when there are 1.5 stop bits.
```

```
If InStr(Settings, ".") > 0 Then
    Offset = 2
```

```

Else
    Offset = 0
End If

cboSpeed.Text = Left$(Settings, Len(Settings) - 6 - Offset)
Select Case Mid$(Settings, Len(Settings) - 4 - Offset, 1)
Case "e"
    cboParity.ListIndex = 0
Case "m"
    cboParity.ListIndex = 1
Case "n"
    cboParity.ListIndex = 2
Case "o"
    cboParity.ListIndex = 3
Case "s"
    cboParity.ListIndex = 4
End Select

cboDataBits.Text = Mid$(Settings, Len(Settings) - 2 - Offset, 1)
cboStopBits.Text = Right$(Settings, 1 + Offset)

cboPort.ListIndex = Form5.MSComm1.CommPort - 1

optFlow(Form5.MSComm1.Handshaking).Value = True
If Echo Then
    optEcho(1).Value = True
Else
    optEcho(0).Value = True
End If

End Sub

Private Sub cmdCancel_Click()
Unload Me
End Sub

Private Sub cmdOK_Click()
Dim OldPort As Integer, ReOpen As Boolean

On Error Resume Next

Echo = iTempEcho
OldPort = Form5.MSComm1.CommPort
NewPort = cboPort.ListIndex + 1

```

```

If NewPort <> OldPort Then      ' If the port number changes, close the old port.
  If Form5.MSComm1.PortOpen Then
    Form5.MSComm1.PortOpen = False
    ReOpen = True
  End If

  Form5.MSComm1.CommPort = NewPort      ' Set the new port number.

  If Err = 0 Then
    If ReOpen Then
      Form5.MSComm1.PortOpen = True
      Form5.mopen.Checked = Form5.MSComm1.PortOpen
      Form5.mnuSendText.Enabled = Form5.MSComm1.PortOpen
      Form5.tbrToolBar.Buttons("TransmitTextFile").Enabled =
frmTerminal.MSComm1.PortOpen
    End If
  End If

  If Err Then
    MsgBox Error$, 48
    Form5.MSComm1.CommPort = OldPort
    Exit Sub
  End If
End If

Form5.MSComm1.Settings = Trim$(cboSpeed.Text) & "," & Left$(cboParity.Text, 1) _
& "," & Trim$(cboDataBits.Text) & "," & Trim$(cboStopBits.Text)

If Err Then
  MsgBox Error$, 48
  Exit Sub
End If

Form5.MSComm1.Handshaking = iFlow
If Err Then
  MsgBox Error$, 48
  Exit Sub
End If

SaveSetting App.Title, "Properties", "Settings", Form5.MSComm1.Settings
SaveSetting App.Title, "Properties", "CommPort", Form5.MSComm1.CommPort
SaveSetting App.Title, "Properties", "Handshaking", Form5.MSComm1.Handshaking
SaveSetting App.Title, "Properties", "Echo", Echo

Unload Me

```

End Sub

Private Sub Form\_Load()

' Set the form's size

Me.Left = (Screen.Width - Me.Width) / 2

Me.Top = (Screen.Height - Me.Height) / 2

' Size the frame to fit in the tabstrip control

fraSettings.Move tabSettings.ClientLeft, tabSettings.ClientTop

' Make sure the frame is the top most control

fraSettings.ZOrder

' Load current property settings

LoadPropertySettings

End Sub

Private Sub optEcho\_Click(Index As Integer)

If Index = 1 Then

    iTempEcho = True

Else

    iTempEcho = False

End If

End Sub

Private Sub optFlow\_Click(Index As Integer)

iFlow = Index

End Sub

CANCEL:

DefInt A-Z

Option Explicit

Dim cancelsend

Const SWP\_NOMOVE = &H2

Const SWP\_NOSIZE = &H1

Private Sub Command1\_Click()

    cancelsend = True

End Sub

Private Sub Form\_Activate()

' Make this form a floating window that is always on top.

```
SetWindowPos hWnd, -1, 0, 0, 0, 0, SWP_NOMOVE Or SWP_NOSIZE  
End Sub
```

```
Private Sub Form_Deactivate()  
If cancelSend = False Then  
Form7.Show  
End If  
End Sub
```

## LOGIN

```
<html>
<head>
<title>login form</title>
</head>
<body bgcolor=RGB(213,213,255) text="white" topmargin=0>
<BR><center>
<img src=title.jpg></center><BR>

<table height=20 width=100% bgcolor=navy cellpadding=0 border=1>
<Tr><Td><center>
<font face=verdana color=white size=1><b> Home |
Login |
Settings |
Living Room |
Office Room |
Bed Room |
Kitchen |
Log File |
Logout
</td></tr></table>

<form method="post" action="http:\\localhost\\nithya\\login.asp">
<br><br>
<table border=1 align=right>
<tr> <td><font face=verdana color=000000 size=1><b>Login Name:</b></td>
<td><input name="username" type=text ></td>
</tr><tr>
<td><font face=verdana color=000000 size=1><b>Enter Password:</b></td>
<td><input name="passwrđ" type=password passwordchar="&" ></td>
</tr><tr colspan=2>
<TD>
<td><input type="submit" value="login "><input type="reset"></td>
</tr></table>

<BR><BR><BR><BR><BR><BR><BR><BR><BR><BR><BR><BR>

<table height=20 width=100% bgcolor=navy cellpadding=0 border=1>
<Tr><Td><center>
<font face=verdana color=white size=1><b> Home |
Login |
Settings |
Living Room |
Office Room |
Bed Room |
Kitchen |
Log File |
Logout
</td></tr></table>
```

## LIVING ROOM

```
<html>
<head>
  <title>login form</title>
  <script language="vbscript">

    sub status
      dim fso
      dim fl,a
      dim form1
      Set form1=document.form1
      Set fso=CreateObject("Scripting.FileSystemObject")
      set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",1)
      a=fl.read(2)
      if a="ON" then
        msgbox "light is On"
      else
        msgbox "light is Off"
      end if
    end sub

    sub change
      dim fso
      dim fl,a
      dim form1
      Set form1=document.form1
      Set fso=CreateObject("Scripting.FileSystemObject")
      set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",1)
      a=fl.read(3)
    msgbox a
      fl.cbse
      set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",2)
    msgbox a
      if a="ON" then
        fl.writeline "OFF"
        msgbox "u switched the light off"
      elseif a="OFF" then
        fl.write "ON"
        msgbox "u switched on the light"
      end if
      fl.close
    end sub

  </script>
</head>
  <body bgcolor=RGB(213,213,255) text="white" topmargin=0>
  <BR><center>
  <img src=title.jpg></center><BR>
<table height=20 width=100% bgcolor=navy cellpadding=0 cellspacing=0 border=1>
```

```

<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officerroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table><BR>

```

```

<center><font face=verdana size=2 color=navy><B>Living Room</b>
<form method="post" name="form1" >
<br><br>

```

```

<table border=1 align=center width=80% cellspacing=5 cellpadding=5>
<tr>
<td><font face=verdana color=000000
size=1><center><b>Television</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Light</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Bulb</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>VCR</b></center></td>
</tr>
<tr>
<td><center><input type=submit value="getstatus" OnClick="status"
></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
</tr>
<tr>
<td><center><input type=submit value="setstatus"
OnClick="change"></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
</tr>
</table>
</form>

```

```

<BR><BR><BR><BR>

```

```
<table height=20 width=100% bgcolor=navy cellspacing=5 cellpadding=5 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table><BR>

</body>
</html>
```

## OFFICE ROOM

```
<html>
<head>
<title>login form</title>
<script language="vbscript">
sub status
dim fso
dim fl,a
dim form1
Set form1=document.form1
Set fso=CreateObject("Scripting.FileSystemObject")
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",1)
a=f1.read(3)
if a="on" then
msgbox "light is on"
else
  msgbox "light is off"
end if
end sub
sub change

dim fso
dim fl,a
dim form1
Set form1=document.form1
Set fso=CreateObject("Scripting.FileSystemObject")
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",1)
a=f1.read(3)

fl.close
if a="on" then
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",2)
fl.writeline "off"
msgbox "u switched the light off"
elseif a="off" then
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",2)

fl.write "on"
msgbox "u switched on the light"
end if
end sub

</script>
</head>
<body bgcolor=RGB(213,213,255) text="white" topmargin=0>
<BR><center>
<img src=title.jpg></center><BR>
<table height=20 width=100% bgcolor=navy cellpadding=0 cellspacing=0 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>
```

```

<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table><BR>
<center><font face=verdana size=2 color=navy><B>Office Room</b>
<form method="post" name="form1" >
<br><br>

```

```

<table border=1 align=center width=80% cellspacing=5 cellpadding=5>
<tr>
<td><font face=verdana color=000000
size=1><center><b>Computer</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Light</b></center></td>
<td><font face=verdana color=000000 size=1><center><b>Music
system</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Bulb</b></center></td>
</tr>
<tr>
<td><center><input type=submit value="getstatus" OnClick="status"
></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
</tr>
<tr>
<td><center><input type=submit value="setstatus"
OnClick="change"></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
</tr>
</table>
</form>
<BR><BR><BR><BR>

```

```

<table height=20 width=100% bgcolor=navy cellspacing=5 cellpadding=5 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |

```

```
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table><BR>
```

```
</body>
</html>
```

## BED ROOM

```
<html>
<head>
<title>login form</title>
<script language="vbscript">
sub status
dim fso
dim fl,a
dim form1
Set form1=document.form1
Set fso=CreateObject("Scripting.FileSystemObject")
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",1)
a=fl.read(3)
if a="on" then
msgbox "light is on"
else
msgbox "light is off"
end if
end sub
sub change

dim fso
dim fl,a
dim form1
Set form1=document.form1
Set fso=CreateObject("Scripting.FileSystemObject")
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",1)
a=fl.read(3)

fl.close
if a="on" then
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",2)
fl.writeline "off"
msgbox "u switched the light off"
elseif a="off" then
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",2)

fl.write "on"
msgbox "u switched on the light"
end if
end sub

</script>
</head>
<body bgcolor=RGB(213,213,255) text="white" topmargin=0>
<BR><center>
<img src=title.jpg></center><BR>
<table height=20 width=100% bgcolor=navy cellspacing=0 cellpadding=0 border=1>
<tr><td><center>
```

```

<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table><BR>
<center><font face=verdana size=2 color=navy><B>Bedroom</b>
<form method="post" name="form1" >
<br><br>

```

```

<table border=1 align=center width=80% cellspacing=5 cellpadding=5>
<tr>
<td><font face=verdana color=000000 size=1><center><b>Audio
system</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Light</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Bulb</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>A/C</b></center></td>
</tr>
<tr>
<td><center><input type=submit value="getstatus" OnClick="status"
></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
</tr>
<tr>
<td><center><input type=submit value="setstatus"
OnClick="change"></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
</tr>
</table>
</form>
<BR><BR><BR><BR>

```

```

<table height=20 width=100% bgcolor=navy cellspacing=5 cellpadding=5 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |

```

```
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table><BR>
```

```
</body>
</html>
```

## KITCHEN

```
<html>
<head>
<title>login form</title>
<script language="vbscript">
sub status
dim fso
dim fl,a
dim form1
Set form1=document.form1
Set fso=CreateObject("Scripting.FileSystemObject")
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",1)
a=f1.read(3)
if a="on" then
msgbox "light is on"
else
  msgbox "light is off"
end if
end sub
sub change

dim fso
dim fl,a
dim form1
Set form1=document.form1
Set fso=CreateObject("Scripting.FileSystemObject")
set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",1)
a=f1.read(3)

fl.close
if a="on" then
  set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",2)
  fl.writeline "off"
  msgbox "u switched the light off"
elseif a="off" then
  set fl=fso.opentextfile("c:\inetpub\wwwroot\nithya\sam.txt",2)

  fl.write "on"
  msgbox "u switched on the light"
end if
end sub

</script>
</head>
<body bgcolor=RGB(213,213,255) text="white" topmargin=0>
<BR><center>
<img src=title.jpg></center><BR>
<table height=20 width=100% bgcolor=navy cellpadding=0 cellspacing=0 border=1>
<Tr><Td><center>
```

```

<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table><BR>
<center><font face=verdana size=2 color=navy><B>Kitchen</b>
<form method="post" name="form1" >
<br><br>

```

```

<table border=1 align=center width=80% cellspacing=5 cellpadding=5>
<tr>
<td><font face=verdana color=000000
size=1><center><b>Chimney</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Stove</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Bulb</b></center></td>
<td><font face=verdana color=000000
size=1><center><b>Fridge</b></center></td>
</tr>
<tr>
<td><center><input type=submit value="getstatus" OnClick="status"
></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
<td><center><input type=submit value="getstatus" ></center></td>
</tr>
<tr>
<td><center><input type=submit value="setstatus"
OnClick="change"></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
<td><center><input type=submit value="setstatus" ></center></td>
</tr>
</table>
</form>
<BR><BR><BR><BR>

```

```

<table height=20 width=100% bgcolor=navy cellspacing=5 cellpadding=5 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |

```

```
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officerroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table><BR>
```

```
</body>
```

```
</html>
```

## SETTINGS

```
<html>
<head>
<title>login form</title>
</head>
<body bgcolor=RGB(213,213,255) text="white" topmargin=0>
<BR><center>
<img src=title.jpg></center><BR>

<table height=20 width=100% bgcolor=navy cellspacing=0 cellpadding=0 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="C:\inetpub\wwwroot\Nithya\livingroom.html "><font face=verdana
color=white size=1><b> Living Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table>
<BR><BR><BR><BR><BR><BR>

<table height=20 width=100% bgcolor=navy cellspacing=0 cellpadding=0 border=1>
<tr><th>
<font face=verdana color=white size=2><b><u>OFFICEROOM
<th> <font face=verdana color=white size=2><b><u>BEDROOM
<th><font face=verdana color=white size=2><b><u>LIVING ROOM
<th><font face=verdana color=white size=2><b><u>KITCHEN
</tr>
<tr><td>
<font face=verdana color=white size=1><b>COMPUTER
<td> <font face=verdana color=white size=1><b>AUDIO SYSTEM
<td><font face=verdana color=white size=1><b>TELEVISION
<td><font face=verdana color=white size=1><b>CHIMNEY
</tr>
<TR>
<td>
<font face=verdana color=white size=1><b>LIGHT
<td> <font face=verdana color=white size=1><b>LIGHT
<td><font face=verdana color=white size=1><b>LIGHT
<td><font face=verdana color=white size=1><b>STOVE
</tr>
<TR>
<td>
<font face=verdana color=white size=1><b>MUSIC SYSTEM
<td> <font face=verdana color=white size=1><b>BULB
```

```

</tr>
<TR>
<td>
<font face=verdana color=white size=1><b>BULB
<td> <font face=verdana color=white size=1><b>A/C
<td><font face=verdana color=white size=1><b>VCR
<td><font face=verdana color=white size=1><b>FRIDGE
</tr></TABLE>
<BR><BR><BR><BR><BR><BR>
<table height=20 width=100% bgcolor=navy cellspacing=0 cellpadding=0 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.html"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officerroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table>
</body>
</html>

```

## SETTINGS

```
<html>
<head>
<title>login form</title>
</head>
<body bgcolor=RGB(213,213,255) text="white" topmargin=0>
<BR><center>
<img src=title.jpg></center><BR>

<table height=20 width=100% bg color=navy cellpadding=0 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="C:\inetpub\wwwroot\Nithya\livingroom.html "><font face=verdana
color=white size=1><b> Living Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table>
<BR><BR><BR><BR><BR><BR>

<table height=20 width=100% bg color=navy cellpadding=0 border=1>
<tr><th>
<font face=verdana color=white size=2><b><u>OFFICEROOM
<th> <font face=verdana color=white size=2><b><u>BEDROOM
<th><font face=verdana color=white size=2><b><u>LIVING ROOM
<th><font face=verdana color=white size=2><b><u>KITCHEN
</tr>
<tr><td>
<font face=verdana color=white size=1><b>COMPUTER
<td> <font face=verdana color=white size=1><b>AUDIO SYSTEM
<td><font face=verdana color=white size=1><b>TELEVISION
<td><font face=verdana color=white size=1><b>CHIMNEY
</tr>
<TR>
<td>
<font face=verdana color=white size=1><b>LIGHT
<td> <font face=verdana color=white size=1><b>LIGHT
<td><font face=verdana color=white size=1><b>LIGHT
<td><font face=verdana color=white size=1><b>STOVE
</tr>
<TR>
<td>
<font face=verdana color=white size=1><b>MUSIC SYSTEM
<td> <font face=verdana color=white size=1><b>BULB
```

## LOGOUT

```
<html>
<head>
<title>login form</title>
</head>
<body bgcolor=RGB(213,213,255) text="white" topmargin=0>
<BR><center>
<img src=title.jpg></center><BR>

<table height=20 width=100% bg color=navy cellpadding=0 cellspacing=0 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.asp"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table>
<BR><BR><BR><BR><BR><BR>
<TABLE align=center border=2 cellpadding=0 cellspacing=0 width="20%">
<form method="post" action="http://localhost/nithya/logout.asp">
<TR bgcolor=navy>
<TD><center><input type="submit" value="Logout
completely"></center></TD></form>
</TR></table>
<BR><BR><BR><BR><BR><BR><BR><BR><BR>
<table height=20 width=100% bg color=navy cellpadding=0 cellspacing=0 border=1>
<Tr><Td><center>
<a href="login.html"><font face=verdana color=white size=1><b> Home </a>|
<a href="login.html"><font face=verdana color=white size=1><b> Login</a> |
<a href="settings.html"><font face=verdana color=white size=1><b> Settings</a> |
<a href="livingroom.asp"><font face=verdana color=white size=1><b> Living
Room</a> |
<a href="officeroom.html"><font face=verdana color=white size=1><b> Office
Room</a> |
<a href="bedroom.html"><font face=verdana color=white size=1><b> Bed
Room</a> |
<a href="kitchen.html"><font face=verdana color=white size=1><b> Kitchen</a> |
<a href="logview.html"><font face=verdana color=white size=1><b> Log File</a> |
<a href="logout.html"><font face=verdana color=white size=1><b> Logout</a>
</td></tr></table>
</body>
</html>
```

## GLOSSARY OF TERMS

API	-	Application Programming Interface
ASP	-	Active Server Page
CGI	-	Common Gateway Interface
COM	-	Component Object Model
GUI	-	Graphical User Interface
HTML	-	Hyper Text Markup Language
HTTP	-	Hyper Text Transfer Protocol
IC	-	Integrated Chip
LAN	-	Local Area Network
PPP	-	Point to Point Protocol
VB	-	Visual Basic
WAN	-	Wide Area Network

## REFERENCES

- ❖ Stephen and Steven Banick," Active Server pages 2.0 unleashed",Macmillan Computer publishing, 1999.
  
- ❖ Greg Perry," Teach Yourself Visual Basic 6", G.C. Jain for Techmedia,1999