



- |     |   |     |                   |
|-----|---|-----|-------------------|
| 8.  | The minimum slope of the hopper bottom of a bunker                              | CO4 | [K <sub>1</sub> ] |
|     | a) 30°  |     |                   |
|     | b) 60°  |     |                   |
|     | c) 45°  |     |                   |
|     | d) 50°  |     |                   |
| 9.  | Purpose of using composite beam is  | CO5 | [K <sub>2</sub> ] |
|     | a) To increase the weight of the structure                                      |     |                   |
|     | b) To decrease the strength of the structure                                    |     |                   |
|     | c) To increase the stiffness of the structure                                   |     |                   |
|     | d) To decrease the load-carrying capacity of the structure                      |     |                   |
| 10. | the minimum compressive strength of the infill material in an encased column is | CO5 | [K <sub>1</sub> ] |
|     | a) 15 MPa   |     |                   |
|     | b) 25 MPa   |     |                   |
|     | c) 20 MPa   |     |                   |
|     | d) 30 MPa   |     |                   |

**PART B (10 x 2 = 20 Marks)**

- |     |  |     |                   |
|-----|--|-----|-------------------|
| 11. | List the types of stiffeners using in the steel structure.   | CO1 | [K <sub>1</sub> ] |
| 12. | Compare framed connection with seated connection.  | CO1 | [K <sub>2</sub> ] |
| 13. | As per IS 800:2007, how the steel cross sections are classified.   | CO1 | [K <sub>1</sub> ] |
| 14. | What do you understand from combined stress in steel sections  | CO1 | [K <sub>2</sub> ] |
| 15. | Pen down the advantages and disadvantages of transmission tower  | CO3 | [K <sub>2</sub> ] |
| 16. | How does wind speed affect the sag in transmission line?   | CO3 | [K <sub>1</sub> ] |
| 17. | What is the impact of using the Gust factor method on the design of chimneys?  | CO4 | [K <sub>2</sub> ] |
| 18. | Mention the design and construction considerations that can be implemented to mitigate the stress on a chimney during an earthquake. | CO4 | [K <sub>2</sub> ] |
| 19. | In terms of the materials used, how are composite beams classified?  | CO5 | [K <sub>1</sub> ] |
| 20. | In what ways does the behavior of a uniaxial eccentric composite column differ from that of a biaxial eccentric composite column?    | CO5 | [K <sub>2</sub> ] |

**PART C (6 x 5 = 30 Marks)**

- |     |  |     |                   |
|-----|--|-----|-------------------|
| 21. | Write a short note on key principles of semi-rigid connections   | CO1 | [K <sub>2</sub> ] |
| 22. | Outline effective width concept of a steel element.  | CO2 | [K <sub>2</sub> ] |
| 23. | Explain the safety factors that need to be considered while calculating the load capacity of Z-purlins with lips and wall studs, emphasizing their significance. | CO2 | [K <sub>2</sub> ] |
| 24. | What are the considerations to be done in design of transmission towers?   | CO3 | [K <sub>3</sub> ] |
| 25. | Compare self-supporting chimney with guyed steel chimney.  | CO4 | [K <sub>2</sub> ] |
| 26. | Explain in detail about the composite slab.  | CO5 | [K <sub>2</sub> ] |

**Answer any FOUR Questions**

**PART D (4 x 10 = 40 Marks)**

27. Calculate the strength and efficiency of a lap joint used to connect two plates of 12 mm thickness using 22mm dia – 6no's power driven shop rivets. Take pitch distance =80 mm, edge distance = 45 mm and  $f_y = 250 \text{ N/mm}^2$  CO1 [K<sub>3</sub>]
28. Design a bridge truss diagonal subjected to a factored tensile load of 300kN. The length of the diagonal is 3m. The tension member is connected to a gusset plate of 16 mm thick with one line of 20 mm dia bolts of grade 8.8 CO2 [K<sub>3</sub>]
29. A simply supported steel beam of 4m effective span is laterally supported throughout. It carries a lateral UDL of 10kN/m. Design an appropriate section using Fe410 grade steel. CO2 [K<sub>3</sub>]
30. Explain the step by step procedures for the self-supported steel chimney of height 70 m and diameter 2.5 m located in the outskirts Coimbatore. Assume II terrain category and flat topography at site. CO4 [K<sub>2</sub>]
31. Design a simply supported composite beam with 8m span spaced at 2.5 m c/c. The thickness of slab is 125 mm. The floor is to carry an imposed load of 2.0 kN/m<sup>2</sup>, partition load of 1.5 kN/m<sup>2</sup> and a floor finish load of 0.5 kN/m<sup>2</sup>. Check the adequacy of section against bending moment if ISMB 450 is used. CO5 [K<sub>3</sub>]

\*\*\*\*\*